




(1)









N	O.	ΤF	S:
	~	. –	.

MATERIAL: HOUSING: SHELL: CONTACT:	THERMOPLASTIC POLYESTER, UL94V-(STEEL, TIN PLATED COPPER ALLOY, 30µ GOLD PLATED)
OPERATING TEMPERATURE:	-55°C ~ 125°C	
POWER/CO-AX CONTACT RATING: (IF PRESENT) SIGNAL CONTACT CURRENT RATING: SIGNAL CONTACT RESISTANCE:	20A (CURRENT) 5A PER CONTACT 10mΩ MAX.	
INSULATOR RESISTANCE: DIELECTRIC	5000MΩ min.	J

COMBINATION D-SUB THESE DRAWINGS AND SPECIFICATIONS EDAC INC ARE THE PROPERTY OF EDAC INC..AND NTO, ONTARIO SHALL NOT BE REPRODUCED, OR COPIED

1000V AC rms



THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.

		A		
``	YOUR CC	NNEC1	ION TO	D QUALIT

WITHSTANDING VOLTAGE:

OR USED AS THE BASIS FOR THE CANADA MANUFACTURE OR SALE OF APPARATUS TY & SERVICE WITHOUT WRITTEN PERMISSION.

SW REFERENCE NO.: 630 COMBO ASSEMBLY				
DRAWN: C.B	DATE: JAN. 01/2019			
CHECKED:	DATE:			
SCALE: (IN C.A.D. 1:1)	SHEET 1 OF 2			
DRAWING NUMBER: 630-2WK	2640-2TA ISSUE			
PART NUMBER: 630-2WK	2640-2TA ¹			

