

Product Search Data Sheet

GRM0335C2A8R4WA01D

In Production RoHS REACH 125

< List of part numbers with package codes > GRM0335C2A8R4WA01D GRM0335C2A8R4WA01W



Applications

| Unsuitable | Please be sure to read and comply with |
|--------------|---|
| Applications | these "Precautions for use." |
| | |
| | performance and reliability of the actual |
| | Product. |

GRM0335C2A8R4WA01J




| Packaging | Specifications | Standard Packing Quantity |
|-----------|--------------------------------|---------------------------------|
| D | φ180mm Reel Paper Tape | 15000 |
| W | φ180mm Reel W8P1 Paper Tape | 30000 |
| J | φ330mm Reel Paper Tape | 50000 |

| Mass (typ.) | | |
|-------------|--------|--|
| 1 piece | 0.33mg | |

Appearance & Shape





1 of 2

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



Note: This datasheet may be out of date. Please download the latest datasheet of GRM0335C2A8R4WA01# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=GRM0335C2A8R4WA01%23

"#" indicates a package specification code.



GRM0335C2A8R4WA01D

Note: This datasheet may be out of date. Please download the latest datasheet of GRM0335C2A8R4WA01# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=GRM0335C2A8R4WA01%23

"#" indicates a package specification code.



Specifications

| Length | 0.6±0.03mm |
|--|---------------|
| Width | 0.3±0.03mm |
| Thickness | 0.3±0.03mm |
| Capacitance | 8.4pF ±0.05pF |
| Distance between external terminals g | 0.2mm min. |
| External terminal size e | 0.1 to 0.2mm |
| Operating Temperature Range | -55℃ to 125℃ |
| Rated Voltage | 100Vdc |
| Size code in inch(mm) | 0201 (0603M) |
| ТС | 0±30ppm/°C |
| Temperature characteristics (complied standard) | C0G(EIA) |
| Temperature range of temperature characteristics | 25℃ to 125℃ |

2 of 2

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.