

Specification Sheet

Part Number: MP3M3.NN3P



Cable Tie Mounting Plate, .50" x 4.25", T18-T50 Cable Ties, #6 (M3) Screw, PA66, Natural, 100/pkg

| | |
|--------------------------------|---|
| Article Number | 151-24319 |
| Type | MP3M3 |
| Color | Natural (NA) |
| Features & Benefits | <ul style="list-style-type: none">•Mounting plates allow multiple bundles to run parallel.•The mounts are secured using two screws, while the bundles are attached using cable ties in any of the available slots. |
| Quantity Per | bag |
| Product Description | Mounting Plates allow multiple cables to be run in parallel. Mounts are secured with two screws. Cables are attached to the plates by running a cable tie through any of the available slots. |
| Short Description | Cable Tie Mounting Plate, .50" x 4.25", T18-T50 Cable Ties, #6 (M3) Screw, PA66, Natural, 100/pkg |

Global Part Name

MP3M3-PA66-NA

Length L (Imperial)

4.25

Length L (Metric)

108.0

Fixation Method

Screw Mounting and Rivet

Width W (Imperial)

0.5

Width W (Metric)

12.7

Cable Ties

T18 - T50

Height H (Imperial)

0.125

Height H (Metric)

3.2

Cable Tie Width Max (Imperial)

0.2

Cable Tie Width Max (Metric)

5.2

Mounting Hole Diameter D (Imperial)

0.15

Mounting Hole Diameter D (Metric)

3.7 mm

Mounting Hole Diameter D Max (Metric)

3.7

Mounting Hole Centers (Imperial)

1.25

| | |
|--|----------------------------------|
| Material | Polyamide 6.6 (PA66) |
| Material Shortcut | PA66 |
| Flammability | UL 94 V2 |
| Operating Temperature (Metric) | -40°F to +185°F (-40°C to +85°C) |
| Reach Complaint(Article 33) | Yes |
| ROHS Complaint | Yes |
| Certification/Specification WEB | RATP NF EN [45545-2] |
| Package Quantity(Imperial) | 100 |
| Package Quantity (Metric) | 100 |
| Customs Number | 3926909988 |
| Content Unit(BMEcat) | pcs. |