



# METAL REDUCERS

## METRIC & PG THREAD

Reducers are ideal when a threaded hole exists and you need to secure a smaller thread or different style of thread. Made of nickel plated brass, SAB's reducers are very durable.

### Technical details:

**Material:** Brass, Nickel Plated  
**Attachment thread:** EN 60423 (Metric)  
 DIN 40430 (PG)



Part Number	Thread Type OT (male)	Thread Type IT (female)	Inner Thread Length ITL (mm)	Outer Thread Length OTL (mm)	Outer Diameter OD (mm)
<b>PG-PG</b>					
RED-01	PG 9	PG 7	8.5	6.0	17.0
RED-02	PG 11	PG 7	9.0	6.0	20.0
RED-03	PG 11	PG 9	9.0	6.0	20.0
RED-04	PG 13.5	PG 7	9.0	6.5	22.0
RED-05	PG 13.5	PG 9	9.0	6.5	22.0
RED-06	PG 13.5	PG 11	9.0	6.5	22.0
RED-07	PG 16	PG 7	9.5	6.5	24.0
RED-08	PG 16	PG 9	9.5	6.5	24.0
RED-09	PG 16	PG 11	9.0	6.0	24.0
RED-10	PG 16	PG 13.5	9.0	6.0	24.0
RED-11	PG 21	PG 11	10.0	7.0	30.0
RED-12	PG 21	PG 13.5	10.0	7.0	30.0
RED-13	PG 21	PG 16	10.0	7.0	30.0
RED-14	PG 29	PG 13.5	11.5	8.0	39.0
RED-15	PG 29	PG 16	11.5	8.0	39.0
RED-16	PG 29	PG 21	11.4	8.0	39.0
RED-17	PG 36	PG 21	12.4	9.0	50.0
RED-18	PG 36	PG 29	12.5	9.1	50.0
RED-19	PG 42	PG 29	14.0	10.0	57.0
RED-20	PG 42	PG 36	14.1	10.0	57.0
RED-21	PG 48	PG 36	14.0	10.0	64.0
RED-22	PG 48	PG 42	14.0	10.0	64.0
<b>PG-Metric</b>					
RED-23	PG 16	M20x1.5	9.0	6.0	24.0
RED-24	PG 21	M20x1.5	10.0	7.0	30.0
RED-25	PG 21	M25x1.5	10.0	7.0	30.0
RED-26	PG 29	M25x1.5	11.5	8.0	39.0
<b>Metric-Metric</b>					
RED-27	M16x1.5	M12x1.5	9.5	6.5	18.0
RED-28	M20x1.5	M12x1.5	9.5	6.5	22.0
RED-29	M20x1.5	M16x1.5	9.0	6.5	22.0
RED-30	M25x1.5	M16x1.5	9.0	6.5	28.0
RED-31	M25x1.5	M20x1.5	11.5	7.0	30.0
RED-32	M32x1.5	M20x1.5	11.5	8.0	39.0
RED-33	M32x1.5	M25x1.5	11.5	8.0	39.0
RED-34	M40x1.5	M25x1.5	12.5	9.0	50.0
RED-35	M40x1.5	M32x1.5	12.5	9.0	50.0
RED-36	M50x1.5	M32x1.5	14.0	10.0	64.0
RED-37	M50x1.5	M40x1.5	14.0	10.0	64.0
RED-38	M63x1.5	M40x1.5	18.0	10.0	71.6
RED-39	M63x1.5	M50x1.5	18.0	10.0	71.6