

## Specification Sheet

Part Number: TAG59L-788

LaserTags are sheet fed for easy loading and fast printing.

LaserTags are made with high temperature materials and adhesives so that they will not be affected by the high heat of laser printing.

LaserTags are printable using toner for long term UV exposure.

LaserTags come in a variety of label sizes and types to fit most applications.



Laser Tag Label, 1.5" x 4.0", 14 Per Sheet, PET, White, 3500/pkg

**Article Number** 594-59788

**Type** TAG59L

**Color** White (WH)

**Quantity Per** pack

**Product Description** HellermannTyton white polyester labels are ideal for marking small electrical and electronic components, such as EPROMS', Integrated circuits, as well as the circuit board itself. Printed labels can withstand the soldering process and survive flux removal when the board is washed. HellermannTyton's 788 material is designed for use on flat surfaces and can also be used to identify connectors, buttons and just about anything requiring permanent, general purpose marking.

<b>Short Description</b>	Laser Tag Label, 1.5" x 4.0", 14 Per Sheet, PET, White, 3500/pkg
<b>Global Part Name</b>	TAG59L-788-WH
<b>Width W (Imperial)</b>	4.0
<b>Width W (Metric)</b>	101.6
<b>Thickness T (Metric)</b>	64.0
<b>Height H (Imperial)</b>	1.5
<b>Height H (Metric)</b>	38.1
<b>Material</b>	Type 788, Polyester (788)
<b>Material Shortcut</b>	788
<b>Adhesive</b>	Acrylic
<b>Halogen Free</b>	No
<b>Adhesive Operating Temperature</b>	-40°F to +199°F (-40°C to +93°C)
<b>Operating Temperature</b>	-40°F to +199°F (-40°C to +93°C)
<b>Reach Compliant (Article 33)</b>	Yes

<b>ROHS Compliant</b>	Yes
<b>Package Quantity (Imperial)</b>	3500
<b>Package Quantity (Metric)</b>	3500
<b>Customs Number</b>	3919905060
<b>Labels per Column</b>	7
<b>Labels per Row</b>	2

© 2021 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)