



注記
NOTE

- 1 ウエハーのそりは、長さ 25.4 に対して 0.24 MAX..
CAMBER MUST BE 0.24 MAX. PER 25.4
- △ 全極数が偶数の場合のみ適用。
TO BE APPLIED ONLY WHEN ALL CKTS. ARE EVEN.

49.72	45.72	10-32-1101	5281-10A	10
44.64	40.64	▲ -1091	▲ -09A	9
34.48	30.48	-1071	-07A	7
29.4	25.4	-1061	-06A	6
24.32	20.32	-1051	-05A	5
19.24	15.24	-1041	-04A	4
14.16	10.16	▼ -1031	▼ -03A	3
9.08	5.08	10-32-1021	5281-02A	2
B	A	EDP NO.	ENG. NO.	極数 NO. OF CKTS.

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		CURRENT REV DESC:		molex	
GENERAL TOLERANCES (UNLESS SPECIFIED)		EC NO: 620398			
4 PLACES ±		DRWN: AKUMAR19 2018/12/21		PRODUCT CUSTOMER DRAWING	
3 PLACES ±		CHK'D: GGA 2019/10/18		DOCUMENT NUMBER	
2 PLACES ±		APPR: GGA 2019/10/18		SD-5281-001	
1 PLACE ±		INITIAL REVISION:		DOC TYPE DOC PART REVISION	
0 PLACES ±		DRWN: TYAJIMA01 2014/03/13		PSD 001 J	
ANGULAR TOL ± 1.0°		APPR: NUKITA 2014/03/13		MATERIAL NUMBER	
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		THIRD ANGLE PROJECTION		CUSTOMER	
10 UNDER ±0.15		DRAWING		SHEET NUMBER	
10 OVER 30 UNDER ---		A3-SIZE		SEE TABLE GENERAL MARKET 1 OF 1	
30 OVER ---		SERIES		1 OF 1	