



LAYOUT SHOWN AS EXAMPLE

Keying Shown as example

CHARACTERISTICS

- Standard : Based on MIL-DTL-38999 Series III
- Shell Material : Composite
- Shell Plating : Olive drab Cadmium
- Insulator : Thermoplastic
- Contacts : Copper Alloy
- Seals & Grommet : Silicon Elastomer
- Contact Plating : Gold over copper Alloy 0.8µm minimum
- Durability : 500 Mating cycles
- Delivered with Souriau contacts and Accessories
- Temperature Range : -65°C to +175°C
- Salt Spray : 2000 hours

| Connector dimension | |
|---------------------|----------|
| Dim | Nominal |
| ØS | 48 Max |
| Z' | 31.5 Max |
| VV THREAD | M37x1-6g |

SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)

| | |
|---------|-----------------------------|
| Country | Jurisdiction & Control List |
| FR | Not Listed |

PN: 8D525J43HB

| | | | |
|--------------|------------|--------------------------|-------------------------|
| A | 07-10-2016 | First Release | |
| ISS | DATE | Latest modification - by | MOD N° |
| Designed By: | | Date: | CUSTOMER DRAWING |

TITLE Composite Plug 8D series

| | | | |
|-------|--|----------------------------|-----------------|
| SCALE | | General linear Tolerances: | NPRDS / PROJECT |
| NA | | ±-- | 859 |

SOURIAU WWW.SOURIAU.COM

This document is the property of SOURIAU it must not be reproduced or communicated without permission

| | | | |
|-----------|------------------------------------|--|------------|
| FORMAT | SOURIAU DRG N° 8D525J43HB-C | | SHEET |
| A3 | | | 1/2 |

BASIC SERIES: 8D 5 - 25 J 43 H B

SHELL TYPE : Plug with RFI Shielding

CONTACT TYPE : Standard Crimp Contact

SHELL SIZE : 25

PLATING : J = Olive drab Cadmium

ORIENTATION : B

CONTACT TYPE : PIN (1500 Matings)

CONTACT LAYOUT : 25-43

4
3
2
1

Contact Layout



| Contact position ID | Location | | Contact position ID | Location | |
|---------------------|--------------|--------------|---------------------|-------------|--------------|
| | X-axis (mm) | Y-axis (mm) | | X-axis (mm) | Y-axis (mm) |
| A | +069 (1.75) | +531 (13.49) | Z | -069 (1.75) | +531 (13.49) |
| B | +203 (5.16) | +495 (12.57) | a | +172 (4.37) | +344 (8.74) |
| C | +324 (8.23) | +425 (10.80) | b | +258 (6.55) | +172 (4.37) |
| D | +424 (10.77) | +326 (8.28) | c | +344 (8.74) | +000 (0.00) |
| E | +493 (12.52) | +205 (5.21) | d | +344 (8.74) | -172 (4.37) |
| F | +531 (13.49) | +069 (1.75) | e | +172 (4.37) | -344 (8.74) |
| G | +531 (13.49) | -069 (1.75) | f | +000 (0.00) | -344 (8.74) |
| H | +493 (12.52) | -205 (5.21) | g | -172 (4.37) | -344 (8.74) |
| J | +424 (10.77) | -326 (8.28) | h | -344 (8.74) | -172 (4.37) |
| K | +324 (8.23) | -425 (10.80) | k | -344 (8.74) | +000 (0.00) |
| L | +203 (5.16) | -495 (12.57) | m | -258 (6.55) | +172 (4.37) |
| M | +000 (0.00) | -531 (13.49) | n | -172 (4.37) | +344 (8.74) |
| N | -203 (5.16) | -495 (12.57) | p | +000 (0.00) | +344 (8.74) |
| P | -324 (8.23) | -425 (10.80) | q | +086 (2.18) | +172 (4.37) |
| R | -424 (10.77) | -326 (8.28) | r | +172 (4.37) | +000 (0.00) |
| S | -493 (12.52) | -205 (5.21) | s | +172 (4.37) | -172 (4.37) |
| T | -531 (13.49) | -069 (1.75) | t | +000 (0.00) | -172 (4.37) |
| U | -531 (13.49) | +069 (1.75) | u | -172 (4.37) | -172 (4.37) |
| V | -493 (12.52) | +205 (5.21) | v | -172 (4.37) | +000 (0.00) |
| W | -424 (10.77) | +326 (8.28) | w | -086 (2.18) | +172 (4.37) |
| X | -324 (8.23) | +425 (10.80) | x | +000 (0.00) | +000 (0.00) |
| Y | -203 (5.16) | +495 (12.57) | | | |

| Shell size | Arrangement no. | Number of contacts | Size contacts | Service rating | Contact location | Supersedes |
|------------|-----------------|--------------------|---------------|----------------|---|------------|
| 25 | -43 | 20 23 | 16 20 | I | a,b,c,d,e,f,g,h,k,m, n,p,q,r,s,t,u,v,w,x All others | MS20057-43 |

SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)

| | |
|---------|-----------------------------|
| Country | Jurisdiction & Control List |
| FR | Not Listed |

PN: 8D525J43HB

| | | | |
|----------------|------------------------------------|----------------------------|---|
| A | 07-10-2016 | First Release | |
| ISS | DATE | Latest modification - by | MOD N° |
| Designed By: | | Date: | CUSTOMER DRAWING |
| TITLE | Composite Plug 8D series | | |
| SCALE | | General linear Tolerances: | NPRDS / PROJECT |
| NA | | ±-- | 859 |
| SOURIAU | WWW.SOURIAU.COM | | This document is the property of SOURIAU it must not be reproduced or communicated without permission |
| FORMAT | SOURIAU DRG N° 8D525J43HB-C | | SHEET 2/2 |