


MATERIAL DECLARATION SHEET



Material Number	SRP0612 Series			
Product Line	Shielded SMD Power Inductor			
Compliance Date	2019 / 08 / 26			
RoHS Compliant	YES	MSL	1	

No.	Construction Element(subpart)	Homogeneous Material	Material weight [g]	Homogeneous Material\ Substances	CASRN if applicable	Materials Mass %	Material Mass % of total unit wt.	Subpart mass of total wt. (%)
1	Core	Magnetic alloy powder	0.219	Iron	7439-89-6	56.70	45.990	81.11
				SilicoN	7440-21-3	9.50	7.706	
				Chromium	7440-47-3	7.50	6.083	
				Oxygen	7782-44-7	1.50	1.217	
				Carbon	7440-44-0	0.90	0.730	
				Sulphur	7704-34-9	0.90	0.730	
				Phenol formaldehyde	9003-35-4	9.50	7.706	
				Phosphoric acid	7664-38-2	4.50	3.650	
				Epoxy	25036-25-3	4.50	3.650	
				Polyester	70729-94-1	4.50	3.650	
2	Wire	EDFB-X	0.039	Copper	7440-50-8	92.5	13.361	14.44
				Polyamide Resin	63428-83-1	5.0	0.722	
				Acryl Resin	-	2.5	0.361	
3	Terminal	Ag. C1100	0.009	Copper	7440-50-8	97.5	3.250	3.33
				Silver	7440-22-4	2.5	0.083	
4	Adhesive	JD034-6	0.002	Epoxy resin 1	25085-99-8	25.0	0.185	0.74
				Epoxy resin 2	-	19.0	0.141	
				Dicyanodiamide	461-58-5	8.0	0.059	
				Polyamine	-	5.0	0.037	
				Fumed silica	112945-52-5	1.0	0.007	
				Silica	7631-86-9	42.0	0.311	

MATERIAL DECLARATION SHEET



5	Mark Seal	TAT INDELIBLE INK - STSG	0.001	Synthetic resin	-	75.0	0.285	0.38
				Carbon black	1333-86-4	25.0	0.095	
		Total weight	0.27					

This Document was updated on: 2019/08/26

Important remarks:

1. It is the responsibility of the user to verify they are accessing the latest version.