


C430C182J1G5TA

AxiMax 400 Comm COG, Ceramic, 1800 pF, 5%, 100 VDC, COG, AxiMax, Commercial Standard



| General Information |                             |
|---------------------|-----------------------------|
| Series              | AxiMax 400 Comm C0G         |
| Description         | AxiMax, Commercial Standard |
| RoHS                | Yes                         |
| Termination         | Tin                         |
| AEC-Q200            | No                          |
| Halogen Free        | Yes                         |

| Specifications  |                          |
|---|--------------------------|
| Capacitance   | 1800 pF                  |
| Measurement Condition   | 1 MHz 1.0Vrms            |
| Capacitance Tolerance   | 5%                       |
| Voltage DC  | 100 VDC                  |
| Dielectric Withstanding Voltage                                       | 250 VDC                  |
| Temperature Range   | -55/+125°C               |
| Temperature Coefficient   | COG                      |
| Capacitance Change with Reference to +25°C<br>and 0 VDC Applied (TCC) | 30PPM/C, 1kHz<br>1.0Vrms |
| Dissipation Factor  | 0.1% 1 MHz 1.0Vrms       |
| Aging Rate  | 0% Loss/Decade<br>Hour   |
| Insulation Resistance   | 100 GOhms                |

Click here for the 3D model.

| Dimensions |                        |
|------------|------------------------|
| D          | 3.81mm MAX             |
| L          | 6.1mm MAX              |
| LL         | 25.4mm MIN             |
| F          | 0.51mm +0.025/-0.076mm |
|            |                        |

| Packaging Specifications |           |
|--------------------------|-----------|
| Packaging                | Bulk, Bag |
| Packaging Quantity       | 200       |

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.