

# GMA.1B.063.RG

# SUMMARY

### # Wires



Image is for illustrative purpose only

Series	1B
Termination type	No contacts / Accessory
IP rating	0
AWG wire size	0.00 - 0.00
Cable Ø	6.30 - 7.00 mm
Status	active

### Download

Request a quote Catalog

# **TECHNICAL DETAILS**

### **Mechanics**


Shell Style/Model	GMA*: Bend relief Grey		
Keying	No keying		
Housing Material	Silicone elastomer VMQ		
Variant	G : Gray		
Weight	1.30 g		
Performance			
Configuration			
Insulator	G: PEEK/Pehd		
Rated Current			

### Others

Temp (min / max): -60°C / +200°C Temperature range in water steam: +140°C

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

# DRAWINGS



No keying

### Dimensions

	А	L
mm.	6.3	34
in.	0,25	1,34

## **RECOMMENDED BY LEMO**

Tools

### Cables

150222		
IJOLLL		

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.