

ATGBICS Juniper QFX-QSFP-DACBO-1M Compatible 40G QSFP+ to 4x10G SFP+ Direct Attach Copper Breakout Cable 1m Passive

Brand : ATGBICS

Product code: QFX-QSFP-DACBO-1M-C

Product name : Juniper QFX-QSFP-DACBO-1M Compatible 40G QSFP+ to 4x10G SFP+ Direct Attach Copper Breakout Cable 1m Passive



Juniper QFX-QSFP-DACBO-1M Compatible 40G QSFP+ to 4x10G SFP+ Direct Attach Copper Breakout Cable 1m Passive

[ATGBICS Juniper QFX-QSFP-DACBO-1M Compatible 40G QSFP+ to 4x10G SFP+ Direct Attach Copper Breakout Cable 1m Passive:](#)

ATGBICS QFX-QSFP-DACBO-1M compatible 40GBase QSFP+ to 4x10G SFP+ direct attach breakout cable operates over passive copper with a cable length of 1m. It is suitable for very short distances and provides a cost-efficient way to connect hardware within close proximity racks. This breakout cable connects to 1 x 40G QSFP+ port of a switch on one end and to 4 x 10G SFP+ ports of a switch on the other end. Our product is built to the exact specification of Juniper QFX-QSFP-DACBO-1M= and we proudly offer a compatibility guarantee and lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA Standards and protocols including; 40G InfiniBand 8x DDR, 4x QDR, 10G/40Gigabit Ethernet, Fibre Channel. Connector A is QSFP+ MSA SFF-8436 Compliant and connector B is SFP+ MSA SFF-8431 Compliant.



Features		Features	
Product colour *	Black	Plug and Play	✓
Cable length *	1 m	Certification	CE,FCC
Connector 1 *	QSFP+	Operational conditions	
Connector 2 *	4x SFP+	Operating temperature (T-T)	0 - 70 °C
Connector 1 gender *	Male	Storage temperature (T-T)	-40 - 80 °C
Connector 2 gender *	Male	Operating relative humidity (H-H)	10 - 90%
Jacket material	Polyvinyl chloride (PVC)	Storage relative humidity (H-H)	10 - 85%
Conductor material	Copper	Packaging data	
Ethernet interface type	40 Gigabit Ethernet	Quantity per pack	1 pc(s)
Networking standards	IEEE 802.3ba	Technical details	
AWG wire size	30	Sustainability certificates	RoHS
Data transfer rate	40000 Mbit/s		



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.