

NOTES:

MATERIAL: HOUSING: THERMOPLASTIC SHELL: STEEL, TIN PLATE CONTACT: COPPER ALLOY, O OPERATING TEMPERATURE: -55 °C ~ 125 °C

THERMOPLASTIC POLYESTER, UL94V-0 STEEL, TIN PLATED COPPER ALLOY, GOLD FLASH PLATED

OPERATING TEMPERATURE:-55°C ~ 125°CPOWER/CO-AX CONTACT RATING:40A (CURRENT)(IF PRESENT)SIGNAL CONTACT CURRENT RATING:5A PER CONTACTSIGNAL CONTACT RESISTANCE:10mΩ MAX.


.XX ±0.13

.XXX ±0.05


INSULATOR RESISTANCE: DIELECTRIC WITHSTANDING VOLTAGE:



1000V AC rms



				SW REFERENCE NO.: 630 COMBO ASSEMBLY			
C	COMBINATION D-SUB		DRAWN: C.B		DATE: JAN. 01/2019		
			CHECKED:		DATE:		
	EDAC INC TORONTO, ONTARIO CANADA O QUALITY & SERVICE	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC.,AND SHALL NOT BE REPRODUCED,OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	SCALE: (I	IN C.A.D. 1:1)	SHEET 1 OF	2	
			DRAWING NUMBER: 630-17W2		2250-4T6	ISSUE	
YOUR CONNECTION TO QU			PART NUME	BER: 630-17W2	2250-4T6	1	



THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.

COMPLIANT

