

Number of contacts

# 6-64



## Strain relief clamp/Locking lever

Identification	No. of contacts	Part number	Drawing	Dimensions in mm																												
Strain relief clamp	6	09 18 506 9002	<table border="1"> <thead> <tr> <th>No. of contacts</th> <th>A</th> </tr> </thead> <tbody> <tr><td>6</td><td>12.2</td></tr> <tr><td>10</td><td>17.3</td></tr> <tr><td>14</td><td>22.4</td></tr> <tr><td>16</td><td>24.9</td></tr> <tr><td>20</td><td>30.0</td></tr> <tr><td>24</td><td>35.18</td></tr> <tr><td>26</td><td>37.6</td></tr> <tr><td>30</td><td>42.7</td></tr> <tr><td>34</td><td>47.8</td></tr> <tr><td>40</td><td>55.4</td></tr> <tr><td>50</td><td>68.1</td></tr> <tr><td>60</td><td>80.8</td></tr> <tr><td>64</td><td>85.9</td></tr> </tbody> </table>	No. of contacts	A	6	12.2	10	17.3	14	22.4	16	24.9	20	30.0	24	35.18	26	37.6	30	42.7	34	47.8	40	55.4	50	68.1	60	80.8	64	85.9	
	No. of contacts	A																														
	6	12.2																														
	10	17.3																														
	14	22.4																														
	16	24.9																														
	20	30.0																														
	24	35.18																														
	26	37.6																														
	30	42.7																														
	34	47.8																														
	40	55.4																														
	50	68.1																														
	60	80.8																														
	64	85.9																														
	10	09 18 510 9002																														
	14	09 18 514 9002																														
	16	09 18 516 9002																														
	20	09 18 520 9002																														
	24	09 18 524 9002																														
26	09 18 526 9002																															
30	09 18 530 9002																															
34	09 18 534 9002																															
40	09 18 540 9002																															
50	09 18 550 9002																															
60	09 18 560 9002																															
64	09 18 564 9002																															
with bulk packaging	6	09 18 506 9002 58U <sup>3)</sup>	6	12.2																												
	10	09 18 510 9002 58U <sup>3)</sup>	10	17.3																												
	14	09 18 514 9002 58U <sup>3)</sup>	14	22.4																												
	16	09 18 516 9002 58U <sup>3)</sup>	16	24.9																												
	20	09 18 520 9002 58U <sup>3)</sup>	20	30.0																												
	26	09 18 526 9002 58U <sup>3)</sup>	26	37.6																												
	30	09 18 530 9002 58U <sup>3)</sup>	30	42.7																												
	34	09 18 534 9002 58U <sup>4)</sup>	34	47.8																												
	40	09 18 540 9002 58U <sup>4)</sup>	40	55.4																												
<p><sup>3)</sup> Packaging unit 5,000 pieces</p> <p><sup>4)</sup> Packaging unit 3,000 pieces</p>																																
<b>Locking lever for female connector</b> Only in conjunction with low-profile male header and strain relief  <sup>5)</sup> Packaging unit 100 pieces <sup>6)</sup> Packaging unit 5,000 pieces		09 18 000 9905 <sup>1)5)</sup> 09 18 000 9905 58U <sup>1)6)</sup>		When the security of latching is required and space is a premium, these locking levers can be fitted onto the strain relief of the HARTING female connector. This can then be used in conjunction with male low-profile headers (see pages 08.14 and 08.15).																												
<b>Coding system with loss of contact</b> Code pin  Removal tool for male contacts		09 18 000 9901 <sup>2)</sup>  09 99 000 0133		To avoid cross-plugging adjacent connectors a coding system is required. A code pin is inserted into the appropriate cavity in the female connector. The corresponding male contact is removed by a special removal tool.																												

SEK

1) Order 2 per female connector  
 2) Part number comprises 6 code pins