



- .040 DIA HOLE IS RECOMMENDED FOR P.C. BOARD
- CONNECTOR MATES WITH ANY AMP 26 POSN PLUG
- REPLACEMENT SOCKET AMP# 207684-4
- UL/CSA DESIGNATION STAMPED IN THIS AREA.
- FINISH: CADMIUM PER QQ-P-416
- FINISH: ZINC PLATED PER ASTM-B-633, .000200-.000400 THK WITH SUPPLEMENTARY CHROMATE (Cr3+)

PLATED PER 6	5-208873-1
PLATED PER 5	208873-1
DESCRIPTION	PART NO.

THIS DRAWING IS A CONTROLLED DOCUMENT.		DIN C.C.THOMAS 1-6-88		Tyco Electronics Corporation	
DIMENSIONS: INCHES		CHK F.C.BALLEW III 1-25-88		Harrisburg, Pa 17105-3608	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD		NAME	
0 PLC ± .005		PRODUCT SPEC		AMPLIMITE 26 POSN. RCPT. ASSY., W/ LOADED POSTED CONTACTS SIZE 2, SERIES 90	
1 PLC ± .005		APPLICATION SPEC		SIZE CAGE CODE DRAWING NO	
2 PLC ± .005		WEIGHT		A1 00779 C=208873	
3 PLC ± .005		CUSTOMER DRAWING		SCALE 4:1 SHEET 1 OF 1 REV H	
4 PLC ± .005		RESTRICTED TO			
ANGLES ± .005					
FINISH SEE CALLOUTS					