

4

3

2

1

THIS DRAWING IS UNPUBLISHED

RELEASED FOR PUBLICATION

2015

LOC

DIST

REVISIONS

© COPYRIGHT 2012 BY TE CONNECTIVITY

ALL RIGHTS RESERVED.

P	LTR	DESCRIPTION	DATE	DWN	APVD
NC		NEW RELEASE PER E.O. P21362	29MAY2012	AM	RDR
A		REVISED PER ECO-14-019072	23FEB2015	JA	DM
A1		REVISED PER PCN E-21-000055	13JAN2021	CO	IG
A2		REVISED PER PCN E-20-017587	10MAR2021	CO	IG

7. PART MODIFICATION: THREADED ADAPTER

△6 CONDUIT ADAPTER ACCEPTS EITHER TYPES:
 A. CONDUIT ADAPTER CAP NUT (CN21) AND SEAL RING (SRN21)
 B. BACKSHELL (M902-2243), COMPRESSION NUT (M902-2053), CABLE Ø .430-.570 [10.92-14.78]
 C. BACKSHELL (M902-2244), COMPRESSION NUT (M902-2054), CABLE Ø .570-710 [14.78-18.03]

△5 MATERIAL: PLUG HOUSING/COUPLING RING: PA66 GF10 (BLACK)
 CONDUIT ADAPTER: PA66 GF10 (GREEN, GRAY, BLUE)
 GROMMET: SILICONE (ORANGE-RED)

△4 SEE 0425-021-0000 APPLICATION SPECIFICATION
 A. RECOMMENDED WIRE INSULATION RANGE
 B. CONTACT REMOVAL TOOLS

3. THIS PLUG MATES WITH HDP24-24-91SX-XXXX RECEPTACLE
 X = SEAL TYPE (N,T,E)
 XXXX = MODIFICATION

△2 CAVITY 5 IS WITH CONTACT SIZE 16 AND THE GROMMET IS SEALED.

△1 CONTACTS 4 AND 5 ARE INTERNALLY CONNECTED (BUILT-IN BRIDGE).

NOTES:

TE INTERNAL PN	DEUTSCH PN
HDP26-24-91SE-L015	HDP26-24-91SE-L015

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN 12MAY2012 ALDO MALAGON	TE Connectivity	
DIMENSIONS: INCHES [mm]		CHK 24MAY2012 BRICE BYFORD		
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD 23MAY2012 STEVE BEARD	NAME PLUG, COUPLING RING SIZE 24, -L015 HDP SERIES	
0 PLC ±		PRODUCT SPEC 0425-021-0000	SIZE A3	
1 PLC ±		APPLICATION SPEC △4	CAGE CODE 4AFU8	
2 PLC ±		WEIGHT	DRAWING NO HDP26-24-91SX-L015	
3 PLC ±.015 [.038]			RESTRICTED TO -	
4 PLC ±			SCALE 2:1	
ANGLES ±0°30'0"			SHEET 1 OF 1	
FINISH N/A			REV A2	
MATERIAL △5		Customer Drawing		

1470-19 (3/11)