



specifications

| CRI | Voltage | Ambient Temp (F) | Color Temp | Material | IP Rating | Efficacy | Gross Weight | Beam Angle | Warranty | Case QTY |
|-----|-------------|------------------|------------|------------------------------|-----------|------------|--------------|------------|----------|----------|
| 80 | 100-277 V ⚡ | -40° - 140° | 5000K | copper free aluminum housing | IP 66 | 140 LM / W | 23.37 lbs | 120° | 6 years | 1 pcs |

select your fixture

| Part Number | Color Temp | Consumption | Lumen Output | Emergency Driver | Dimensions |
|--------------------|------------|-------------|--------------|------------------|-------------------|
| GI-EPR-C250-C1D2 | 5000K | 50W | 6,500 | No | 53" x 7.9" x 4.7" |
| GI-EPR-C250-EMC1D2 | 5000K | 50W | 6,500 | Yes | 53" x 7.9" x 4.7" |



Features

- Rated for high temperatures, humidity, dust and vapor locations
- Built for a variety of purposes such as spot light, tunnel light, and general illumination in hazardous locations
- Light weight design
- Heavy duty and high impact resistance
- Various installation options for particular applications
- Non-dimmable

Distribution Diagram

| Center Beam fc | Beam Width | | |
|----------------|------------|-------|-------|
| 17ft | 14fc | 51ft | 51ft |
| 34ft | 3fc | 103ft | 101ft |
| 51ft | 2fc | 154ft | 153ft |
| 68ft | 0.8fc | 256ft | 255ft |
| 85ft | 0.6fc | 307ft | 306ft |

■ Vert, Spread; 120°
■ Horiz, Spread; 120°

Not all product variations listed on this page may be DLC qualified. Visit www.designlights.org/search to confirm qualification.

