


ITEM NO.	PART NUMBER	DESCRIPTION	QTY.	COMPONENT NOTES
1	50-00072	Connector, dc plug, 5.5x2.5xL23.8 mm, molding style, spring contacts, twist lock	1	
2	30-00007	Wire, 2C BC, 18 AWG, UL2468, 300V, 80C, 4.4 mm, VW-1, PVC, 87A	1	
3	24-00055	Overmold, PVC, black	1	



Notes:

Hi-Pot test: 600 Vac, 0.5 mA, 1 second

Wiring Diagram	
50-00072	wire color
center	black with stripe
sleeve	black

Revision:	Date:	Description:	Prepared:	Notes:	<h1>TENSILITY</h1> <p>tel 1.541.323.3228 800 877.670.7118 fax 1.541.323.4202 web tensility.com</p>
A	3/29/2010	Re-issue CUI spec as Tensility	GL 2016.03.17 08:32:27 -07'00'	RoHS compliant	
A1	8/31/2011	Updated description, connector, and wire information	Verified: LA <small>Digitally signed by LA DN: cn=L.A. Srinivasan, ou=Engineering, email=L.A.Srinivasan@tensility.com, c=US Date: 2016.08.31 12:28:10 -0700'</small>	Function test: no open, no short circuit, no intermittent	
			Dimensions are in millimeters. Tolerances: X: ± 0.5 mm X.X: ± 0.3 mm X.XX: ± 0.05 mm	Description: Cable, 1830 mm, 5.5x2.5x12 mm, twist lock 50-00072 dc plug to stripped tinned, 18 AWG, 30-00007 wire	
Size:		Part number:		Scale: 1:1	
A		053-0488R (CA-2223)		Sheet 1 of 1	