

## Specification Sheet

Part Number: T30RA30



Cable Ties for AT2060, 30lb Tensile Strength, PA66, Natural, 30/bandolier, 600/pkg

<b>Article Number</b>	103-00002
<b>Type</b>	T30RA
<b>Color</b>	Natural (NA)
<b>Features &amp; Benefits</b>	<ul style="list-style-type: none"><li>• The AT2060 cable tie system is designed for automatic installation on bundles up to 1.25" and a minimum tensile strength of 30 lbs.</li><li>• Available in reels of 3,000 each or bandoliers of 30 each.</li></ul>
<b>Quantity Per</b>	bag
<b>Product Description</b>	Cable ties for use with HellermannTyton's AT2060 automatic cable tie tool
<b>Short Description</b>	Cable Ties for AT2060, 30lb Tensile Strength, PA66, Natural, 30/bandolier, 600/pkg
<b>Global Part Name</b>	T30RA-PA66-NA

<b>Minimum Tensile Strength (Imperial)</b>	30.0
<b>Minimum Tensile Strength (Metric)</b>	133.4
<b>Length L (Imperial)</b>	6.0
<b>Length L (Metric)</b>	152.4
<b>Identification Plate Position</b>	none
<b>Reel Diameter (Imperial)</b>	17.7
<b>Reel Diameter (Metric)</b>	450.0
<b>Reel Width (Imperial)</b>	7.197
<b>Reel Width (Metric)</b>	182.8
<b>Voltage Range</b>	27 Volt
<b>Releasable Closure</b>	No
<b>Width W (Imperial)</b>	0.14
<b>Width W (Metric)</b>	3.6
<b>Bundle Diameter Min (Imperial)</b>	0.06
<b>Bundle Diameter Min (Metric)</b>	1.5
<b>Bundle Diameter Max (Imperial)</b>	1.25
<b>Bundle Diameter Max (Metric)</b>	31.75

**Cycle Time** 1.2 seconds

**Power Supply** Electrical

**Tension Force** Adjustable

**Material** Polyamide 6.6 (PA66)

**Material Shortcut** PA66

**US MIL SPEC** MS3367-5-9 **Flammability**

UL 94 V2

**Operating Temperature (Metric)**

-40°F to +185°F (-40°C to +85°C)

**Certification/Specification WEB**

UL-ZODZ2.E64139 CAGE Code 53421

**UL Recognized (US)**

Yes

**UL Recognized (US and Canada)**

Yes

**Package Quantity(Imperial)** 600

**Package Quantity (Metric)** 600

**Customs Number** 3926909988

**Weight (Metric)** 1.8

**Weight (Imperial)**

3.9

**Reel Weight (Imperial)**

7

**Reel Weight (Metric)**

3.175