



ØF = Cable diameter

Order-No.	Shell Size / for No. of Contacts	B	C	D	ØF	H	U	V	W
FKH1-09SA-5939	1 / 9	±0.1	±0.3	±0.3	min - max	±0.3	±0.4	±0.15	-0.2
FKH2-15SA-5939	2 / 15	25	31.2	31.8	4.5 - 7	35	30.8	25	16.4
FKH3-25SA-5939	3 / 25	33.3	40	32	4.5 - 7	34.7	39.1	33.3	24.7
		47.04	53.7	35	8 - 10.5	37.7	53	47.04	38.5

FKHY-xxSA-5939

e.g. FKH3-25SA-5939

*1) V for hood size 1, 2 or 3
 *2) xx No. of contacts 09, 15 or 25

RoHS compliant

max. torque are 40 Ncm
 Part-No. 3 to 6 not mounted

reverse side
 1 : 1

No.	St.	Part	Type Description / Material	FRS1 / 5	4 - 40 / Brass	nickel plated
6	2	Knurled thumb screw	Steel	zinc plated		
5	2	Cable clamp screw	Steel	tin plated		
4	1	Cable clamp	Steel	zinc plated		
3	2	Shell screw	FKHy / PC+ABS	black		
2	1	Hood	FxxS0G1A			
1	1	D-Sub Connector	Type Description / Material			
		Part	FRS1 / 5 4 - 40 / Brass			
		SCALE	2:1			
		NAME / DATE				
		DRAWN				
		CHECKED				
		TITLE				
		DWG. NO.				
		REV.				