



**Material**

- Item a Clamp: Brass(CuZn), Ni plated
- Item b Terminal screw: Steel Zinc plating "-" slot type
- Item c Female contact: PbZr(CuSn)Tin plated
- Item d Terminal housing: Thermoplastic (UL94V-0) GREEN(RAL6018/T)

**Electrical** cULus

- Voltage rating: 300V
- Current rating: 10A
- Wire range:
- Solid wire(AWG): 16-28
- Stranded wire(AWG): 16-28
- Torque(Lb-In): 1.7Lb-In
- Screw: M2
- Wire strip length: 5-6mm
- Withstanding Voltage: 1.6KV
- Operating temperature: -40°C to +115°C
- Safety Approval: **cULus**

**DIMENSION**

A	Nx3.81
B	(N-1)x3.81

N=Number of poles

Poles	Dim A&B Tol.
2p-6p	±0.15
7p-12p	±0.25
13p-16p	±0.35
17p-24p	±0.40

**RoHS compliant**  
Unit: mm



Scale	Free
<b>TOLERANCE</b>	
X.	±0.50
X.X	±0.30
X.XX	±0.10
<b>DIM</b>	
TOL	
X.°	±1°
Angle	TOL

Id.	Modification	Date	Name
①	Add UL	18.04.2016	Amy
②	Drawn	19.04.2010	Alex

Date	Name
19.04.2010	Alex
18.04.2016	Amy

Customer-No.	Drawing-No.	Replace
ASSMANN WSW-No.	A-TB381-THXX	
	ASS 4116 CO	rev01
		Sheet



1	2	3	4	5	6	7
H	G	F	E	D	C	B