ATGBICS JL439A HPE Compatible Transceiver SFP+ 10GBase-LR (1310nm, SMF, 10km, DOM)

Brand : ATGBICS

Product code: JL439A-C

Product name : JL439A HPE Compatible Transceiver SFP+ 10GBase-LR (1310nm, SMF, 10km, DOM)

JL439A HPE Compatible Transceiver SFP+ 10GBase-LR (1310nm, SMF, 10km, DOM)


ATGBICS JL439A HPE Compatible Transceiver SFP+ 10GBase-LR (1310nm, SMF, 10km, DOM):

ATGBICS JL439A 10GBase-SR supports a distance of up to 300m over multi-mode fibre (MMF) using a wavelength of 850nm via an LC connector. This product can operate at extended temperatures between -5°C to 85°C. Digital optical monitoring (DOM) support is also present enabling real-time monitoring of the parameters of the fibre optic transceiver. Our product meets the specification of HPE JL439A= for the HPE X130 series. We proudly offer a compatibility guarantee and lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA Standards.





Performance		Features	
SFP transceiver type *Fiber opticMaximum data transfer rate *10000 MbitInterface type *SFP+Single-mode fiber (SMF) supported✓Multi-mode fiber (MMF) supportedXFiber optic connectorLCSFP transceiver standardLR	10000 Mbit/s	Certification	CE, FCC, RoHS
		Power	
	×	Input voltage Maximum voltage Power consumption (typical)	3.3 V 3.5 V 1 W
	P transceiver standard LR aximum transfer distance 10000 m avelength 1310 nm hernet LAN ✓ hernet interface type 10 Gigabit Ethernet gital Diagnostics Monitoring DM) ✓ avelength-division multiplexing /DM) ×	Operational conditions	
Maximum transfer distance Wavelength Ethernet LAN Ethernet interface type Digital Diagnostics Monitoring (DDM) Wavelength-division multiplexing (WDM) Features Product colour		Maximum operating temperature Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Weight & dimensions Width Depth Height Weight	70 °C 0 - 70 °C -40 - 85 °C 0 - 95% 0 - 95% 13.4 mm 56.5 mm 8.5 mm 19 g
Housing material	Metal	Packaging data	19 g
Plug and Play Hot-Plug support Hot-swap Easy to install Country of origin Brand compatibility	V V United Kingdom HP	Number of products included Package type Technical details Sustainability compliance Sustainability certificates Doesn't contain	1 pc(s) Box ✓ RoHS Lead



5056468710826

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.