



NOTES:

1. MATERIALS:
HOUSING - THERMOPLASTIC, BLACK
TERMINALS - COPPER ALLOY, GOLD AND TIN PLATED
SHELL - COPPER ALLOY, NICKEL PLATED
2. ELECTRICAL CHARACTERISTICS:
CONTACT RESISTANCE - 30m OHM MAX
INSULATION RESISTANCE - 1000M OHM MIN @ 500V DC
VOLTAGE AND CURRENT RATING - 1.5A @ 250V AC MIN
DIELECTRIC WITHSTAND VOLTAGE - 750V AC RMS FOR 1MINUTE
3. PRODUCT LIFECYCLE: 1500 INSERTION/WIDTHDRAWAL CYCLES.
4. THIS PART IS RoHS COMPLIANT.

CUSTOMER DRAWING

					THIS DRAWING DESCRIBES A DESIGN CONSIDERED PROPRIETARY IN NATURE, DEVELOPED AND MANUFACTURED BY SWITCHCRAFT INC. AND IS RELEASED ON A CONFIDENTIAL BASIS FOR IDENTIFICATION PURPOSES ONLY.					
					SIZE	WIDTH	MULT	LBS/M	TEMPER	
					FINISH			MATERIAL		
					SPEC No.			SPEC No.		
					FIRST USED ON		SCALE			
					-		3:1			
DATE DRAWN		BY	CHKD		APVD					
8/24/22		TS	TS		TS					
		10/27/22		10/27/22			SHEET 1 OF 1			
REV					NAME			PART No.		
ECO NUMBER					RIGHT ANGLE SMT			RAHUB20		
DATE					TYPE-B USB 2.0, RoHS			REV		
BY					DO NOT SCALE DRAWING					A
APVD										
REVISIONS										