



TG-NSP60

Non-Silicone Thermal Putty

Version 1.060919

Non-Silicone Thermal Putty

TG-NSP60 is an ultra conformable, silicone free putty type gap filler. It is designed for when heat transfer is needed between delicate components where the pressure must be minimised and silicone contamination cannot be tolerated.

TG-NSP60 is designed to fill gaps from 0.25 - 8mm with little or no stress generated. The non-silicone formulation will adhere to all surfaces, such as metal housings, ceramic and plastic IC packages and FR4 boards to give a low thermal resistance path for heat transfer.

TG-NSP60 is available in 30cc or 55cc syringes, pots of 1oz, 4oz, 1lb, or 5lb, and in 20lb or 50lb pails.

Features

- Excellent thermal conductivity 5.9 W/mK
- Fully cured and reworkable
- Ideal for wide range of gaps
- Fully supported optimisation of dispense systems

Applications

- Consumer electronics
- Power supplies and semi-conductors
- Automotive
- LED lighting

Properties

- ✓ REACH Compliant
- ✓ ROHS Compliant

Property	TG-NSP60	Unit	Test Method
Colour	Grey	-	Visual
Thermal Conductivity	5.9	W/mK	ASTM D5470
Working Temperature	-55 to 200	°C	-
Weight Loss	<0.5	%	ASTM E595
Volume Resistivity	2.15×10^{15}	Ohm-cm	ASTM D-257
Thermal Conductivity	4.5	W/mK	ASTM D5470
Volatile Content	<0.5	%	ASTM E595
D4-10	0	PPM	GC/MS

Standard Packaging

Size	Pot	Weight (lbs)
	Syringe	30cc, 55cc
Pot	1oz, 4oz, 1lb, 5lb	
Pail	20lb, 80lb	

Storage

Tightly close original container of unused product. Store in a cool and dark place.

T-Global Technology Limited
1 & 2 Cosford Business Park, Central Park,
Lutterworth, Leicestershire LE17 4QU U.K.

Tel: +44 (0)1455 553 510
Email: sales@tglobaltechnology.com
Web: www.tglobaltechnology.com
Skype: tglobal.technology
VAT #: GB 116 662 714

NOTICE: The information contained herein is to the best of our knowledge true and accurate. However, since the varied conditions of potential use are beyond our control, all recommendations or suggestions are presented without guarantee or responsibility on our part and users should make their own test to determine the suitability of our products in any specific situation. This product is sold without warranty either expressed or implied, of fitness for a particular purpose or otherwise, except that this product shall be of standard quality, and except to the extent otherwise stated in T-Global Technology Europe and North America's invoice, quotation, or order acknowledgment. We disclaim any and all liabilities incurred in connection with the use of information contained herein, or otherwise. All risks of such are assumed by the user. Furthermore, nothing contained herein shall be construed as a recommendation to use any process or to manufacture or to use any product in conflict with existing or future patents covering any product or material or its use.