



PC98 Non Silicone Thermal Interface Material

Version 3.130218

Non Silicone Thermal Interface Material

PC98 is a white, highly filled non-silicone system suitable for thermal dissipation of electronic devices. It has long shelf life even at room temperature of 25°C.

Features

- Unique, non-silicone formulation
- No out-gassing
- Thermal conductivity 5 W/mK
- Hardness of 40 (Shore 00)
- Range of thicknesses available
- Can be cut to custom shapes

Applications

- Heat dissipation from electronic components.
- Cooling of consumer electronics
- Automotive electronics
- Hard drives
- LED lighting systems

Properties

- ✓ REACH Compliant
- ✓ ROHS Compliant

Guidelines for Use

1. Wear rubber gloves when handling the product.
2. Place the product onto the required electronic part and circuit.
3. No heating or curing is required.
4. The product can be applied and removed easily. Care must be taken during installation to avoid tearing.

Storage

Store this non-silicone thermal interface material in an air tight container in a cool (20°C to 30°C), dark place to prolong shelf life. Avoid contact with moisture.

Property	PC98	Unit	Tolerance	Test Method
Chemical type	Non-silicone	-	-	-
Tackiness	No adhesive/1A/2A	-	-	-
Appearance	White	-	-	-
Operating temperature	-40 to 150	°C	-	-
Tensile strength	4.0 – 6.0	kg/cm ²	-	ASTM D412
Elongation	> 80	%	-	ASTM D412
Hardness	40	Shore 00	-	ASTM D2240
Viscosity	Pad	cP	-	ASTM D445
Thermal conductivity	5	Wm-1K-1	-	ASTM D5470
Density	1.5	g/cm ³	-	ASTM D792
Shelf life, 25°C	12	Month	-	-

Part Number Information

Product	Length	Width	Thickness
PC98	288	192	< 1.5mm
	230	230	≥ 1.5mm

* All measurements in mm

T-Global Technology Limited
1 & 2 Cosford Business Park, Central Park,
Lutterworth, Leicestershire LE17 4QU U.K.

Tel: +44 (0)1455 553 510
Email: sales@tglobaltechnology.com
Web: www.tglobaltechnology.com
Skype: tglobal.technology
VAT #: GB 116 662 714

NOTICE: The information contained herein is to the best of our knowledge true and accurate. However, since the varied conditions of potential use are beyond our control, all recommendations or suggestions are presented without guarantee or responsibility on our part and users should make their own test to determine the suitability of our products in any specific situation. This product is sold without warranty either expressed or implied, of fitness for a particular purpose or otherwise, except that this product shall be of standard quality, and except to the extent otherwise stated in T-Global Technology Europe and North America's invoice, quotation, or order acknowledgment. We disclaim any and all liabilities incurred in connection with the use of information contained herein, or otherwise. All risks of such are assumed by the user. Furthermore, nothing contained herein shall be construed as a recommendation to use any process or to manufacture or to use any product in conflict with existing or future patents covering any product or material or its use.