



Main

| | |
|---------------------------|--|
| Range of Product | Harmony XVL |
| Product or Component Type | LED pilot light with black bezel |
| Component name | XVL |
| Mounting diameter | 0.31 in (8 mm) |
| Light source | Protruding LED |
| Light block colour | Yellow |
| Protection Type | Integral ballast resistor Built-in by diode |
| [Us] rated supply voltage | 24 V |
| IP degree of protection | IP40 IEC 60529 IP40 NF C 20-010 |

Complementary

| | |
|-------------------------------|--|
| Supply circuit type | DC |
| Connections - terminals | Tag for Faston connectors 2.8 x 0.5 mm Tag for soldering connectors |
| Current Consumption | 18 mA |
| [Ui] rated insulation voltage | 50 V IEC 60947-1 |
| Bulb lifespan | 100000 h |
| Nominal voltage limit | 0.8...1.1 Un |
| Terminals description ISO n°1 | (X1-X2)PL |
| Height | 0.47 in (12 mm) |
| Width | 0.47 in (12 mm) |
| Depth | 1.34 in (34 mm) |
| Net Weight | 0.01 lb(US) (0.003 kg) |

Environment

| | |
|---------------------------------------|--|
| Product Certifications | UL CSA |
| Protective treatment | TC |
| Ambient air temperature for operation | -13...158 °F (-25...70 °C) |
| Ambient Air Temperature for Storage | -40...158 °F (-40...70 °C) |
| Overvoltage category | Class 3 IEC 60536 Class 3 NF C 20-030 |

Ordering and shipping details

| | |
|-----------------------|------------------------------------|
| Category | 22460 - PUSHBUTTONS 22MM (PLASTIC) |
| Discount Schedule | CS2 |
| GTIN | 3389110651102 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 0.11 oz (3 g) |
| Returnability | No |
| Country of origin | FR |

Packing Units

| | |
|------------------------------|------------------|
| Unit Type of Package 1 | PCE |
| Package 1 Height | 0.47 in (1.2 cm) |
| Package 1 width | 0.47 in (1.2 cm) |
| Package 1 Length | 1.65 in (4.2 cm) |
| Unit Type of Package 2 | BB1 |
| Number of Units in Package 2 | 10 |
| Package 2 Weight | 1.13 oz (32 g) |
| Package 2 Height | 1.18 in (3 cm) |
| Package 2 width | 4.72 in (12 cm) |
| Package 2 Length | 5.51 in (14 cm) |
| Unit Type of Package 3 | S01 |
| Number of Units in Package 3 | 100 |
| Package 3 Weight | 18.52 oz (525 g) |
| Package 3 Height | 5.91 in (15 cm) |
| Package 3 width | 5.91 in (15 cm) |
| Package 3 Length | 15.75 in (40 cm) |

Offer Sustainability


| | |
|----------------------------|--|
| Sustainable offer status | Green Premium product |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |
| Environmental Disclosure | Product Environmental Profile |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

LED Pilot Light

Dimensions




- (1) Tags for Faston connectors or soldered connections
e panel thickness: 1 to 8 mm/0.03 to 0.31 in.

| C | | Ø | |
|----|------|----|------|
| mm | in. | mm | in. |
| 32 | 1.26 | 12 | 0.47 |

LED Pilot Light

Panel Drilling



| Ø min | | G min | | H min | |
|-------|------|-------|------|-------|------|
| mm | in. | mm | in. | mm | in. |
| 8.2 | 0.32 | 12.5 | 0.49 | 12.5 | 0.49 |