


## NOTES:

MATERIAL:	
HOUSING:	THERMOPLAS
SHELL:	STEEL, NICKEI
CONTACT:	COPPER ALLO
OPERATING TEMPERATURE:	-55°C ~ 125°C

.XX ±0.13

.XXX ±0.05

PLASTIC POLYESTER, UL94V-0 **IICKEL PLATED** ALLOY, GOLD FLASH PLATED




NG TEMPERATURE:	-55°
-----------------	------

POWER/CO-AX CONTACT RATING: 30A (CURRENT) (IF PRESENT) SIGNAL CONTACT CURRENT RATING: 5A PER CONTACT SIGNAL CONTACT RESISTANCE:  $10m\Omega$  MAX.

**INSULATOR RESISTANCE:** DIELECTRIC WITHSTANDING VOLTAGE:



COMBINATION D-SUB		SW REFERENCE NO.: 630 COMBO ASSEMBLY		
		DRAWN: C.B	DATE: JAN. 01/201	9
		CHECKED:	DATE:	
EDAC INC ARE THE PROPERTY OF EDAC INC.,AN SHALL NOT BE REPRODUCED, OR COF OR USED AS THE BASIS FOR THE	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INCAND	SCALE: (IN C.A.D. 1:1)	SHEET 1 OF	2
		DRAWING NUMBER: 630-21W1240-3N4 IS		ISSUE
	MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	PART NUMBER: 630-21W	1240-3N4	1





THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.



