



LAYOUT SHOWN AS EXAMPLE

Keying Shown as example

**CHARACTERISTICS**

- Standard : Based on MIL-DTL-38999 Series III
- Shell Material : Stainless Steel
- Shell Plating : Nickel
- Insulator : Thermoplastic
- Contacts : Copper Alloy
- Seals & Grommet : Silicon Elastomer
- Contact Plating : Gold over copper Alloy 0.8µm minimum
- Durability : 500 Mating cycles
- Delivered with Souriau contacts and Accessories
- Temperature Range : -65°C to +200°C
- Salt Spray : 500 hours

| Connector dimension |                 |
|---------------------|-----------------|
| Dim                 | Nominal         |
| A                   | 34.9±0.3        |
| B                   | 19.07+0.1/-0.15 |
| R                   | 32.5Max         |
| S                   | 31.8±0.4        |
| W                   | 2.2+0.9/-0.1    |
| VV THREAD           | M15x1-6g        |

SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)

|         |                             |
|---------|-----------------------------|
| Country | Jurisdiction & Control List |
| FR      | Not Listed                  |

**PN: 8D711S04AC**

|                |   |                            |   |
|----------------|---|----------------------------|---|
| A              | 30-09-2016                                  | First Release              |   |
| ISS            | DATE  | Latest modification - by   | MOD N°  |
| Designed By:   |   | Date:                      | <b>CUSTOMER DRAWING</b>   |
| <b>TITLE</b>   | <b>Stainless Steel Receptacle 8D series</b> |                            |   |
| SCALE          |   | General linear Tolerances: | NPRDS / PROJECT   |
| NA             |   | ±--                        | <b>859</b>  |
| <b>SOURIAU</b> | <b>WWW.SOURIAU.COM</b>                      |                            | This document is the property of SOURIAU it must not be reproduced or communicated without permission |
| FORMAT         | <b>SOURIAU DRG N° 8D711S04AC-C</b>          |                            | SHEET   |
| <b>A3</b>      |   |                            | <b>1/2</b>  |

|                |                                 |   |   |    |   |    |   |   |                 |
|----------------|---------------------------------|---|---|----|---|----|---|---|-----------------|
| BASIC SERIES:  | 8D                              | 7 | - | 11 | S | 04 | A | C | ORIENTATION : C |
| SHELL TYPE :   | Jam nut Receptacle              |   |   |    |   |    |   |   |                 |
| CONTACT TYPE : | Standard Crimp Contact          |   |   |    |   |    |   |   |                 |
| SHELL SIZE :   | 11                              |   |   |    |   |    |   |   |                 |
| PLATING :      | S = Nickel                      |   |   |    |   |    |   |   |                 |
|                | CONTACT TYPE : PIN(500 Matings) |   |   |    |   |    |   |   |                 |
|                | CONTACT LAYOUT : 11-04          |   |   |    |   |    |   |   |                 |

Contact Layout



| Contacts<br>(Insert arrangement 11-4) |                  |             |
|---------------------------------------|------------------|-------------|
| Contact position ID                   | Contact location |             |
|                                       | X-axis (mm)      | Y-axis (mm) |
| A                                     | +065 (1.65)      | +065 (1.65) |
| B                                     | +065 (1.65)      | -065 (1.65) |
| C                                     | -065 (1.65)      | -065 (1.65) |
| D                                     | -065 (1.65)      | +065 (1.65) |

| Shell size | Arrangement no. | Number of contacts | Size contacts | Service rating | Contact location | Supersedes |
|------------|-----------------|--------------------|---------------|----------------|------------------|------------|
| 11         | -4              | 4                  | 20            | I              | All              | MS20050-4  |

Panel cutout

JAM NUT RECEPTACLE (TYPE 7)



| Dim | Nominal       |
|-----|---------------|
| B   | 19.59+0/-0.25 |
| ØC  | 20.96+0.25/-0 |

SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)

| Country | Jurisdiction & Control List |
|---------|-----------------------------|
| FR      | Not Listed                  |

PN: 8D711S04AC

|                |   |                            |   |
|----------------|---|----------------------------|---|
| A              | 30-09-2016                                  | First Release              |   |
| ISS            | DATE  | Latest modification - by   | MOD N°  |
| Designed By:   |   | Date:                      | <b>CUSTOMER DRAWING</b>   |
| <b>TITLE</b>   | <b>Stainless Steel Receptacle 8D series</b> |                            |   |
| SCALE          |   | General linear Tolerances: | NPRDS / PROJECT   |
| NA             |   | ±--                        | <b>859</b>  |
| <b>SOURIAU</b> | <b>WWW.SOURIAU.COM</b>                      |                            | This document is the property of SOURIAU it must not be reproduced or communicated without permission |
| FORMAT         | <b>SOURIAU DRG N° 8D711S04AC-C</b>          |                            | SHEET<br>2/2  |