



Features

- Provides physical protection, with conductive material providing reliable path-to-ground
- Efficient means of transporting items to the assembly area, and empty totes back to the store room for refilling
- Extremely durable; includes steel reinforcing frame and rolled over side construction (double thickness)
- Ships assembled
- Conductive 1×10^2 to $< 1 \times 10^5$ ohms material provides reliable path-to-ground
- Superior strength and durability; made from extruded, high impact polypropylene materials
- Chemical and moisture resistant
- Ideal for use where corrugated and/or paper products cannot be used
- Economical alternative to injection molded products
- Reusable, ensuring best value*
- Made in America

Specifications

Properties

Resin Type
 Conductive
 Surface Resistance
 Humidity Independent
 Temperature Tolerance
 Melting Point

Typical Values

Polypropylene
 Permanently
 1×10^2 to $< 1 \times 10^5$ ohms per ANSI/ESD STM11.11
 Yes
 -17° F to +230° F
 324° F

Part Number	Size O.D. - L x W x D
39140	18" x 12" x 6"
39141	27-1/4" x 12" x 6"
39142	27-1/4" x 18" x 6"

If not otherwise noted, tolerance $\pm 10\%$
 Specifications and procedures subject to change without notice.



Made in the
 United States of America

PLASTEK™ NESTING TOTES

PROTEKTIVE PAK
 13520 MONTE VISTA AVENUE, CHINO, CA 91710
 PHONE (909) 627-2578
ProtektivePak.com

DRAWING NUMBER
 39140

DATE:
 June
 2017

PROTEKTIVE PAK