




10.70 5.80 9.40 2.54

NOTES:

MATERIAL: HOUSING: SHELL: CONTACT:	THERMOPLASTIC POLY STEEL, TIN PLATED COPPER ALLOY, 30µ GO	
OPERATING TEMPERATURE:	-55°C ~ 125°C	
POWER/CO-AX CONTACT RATING: (IF PRESENT)	10A (CURRENT)	
SIGNAL CONTACT CURRENT RATING:	5A PER CONTACT 10mΩ MAX.	
INSULATOR RESISTANCE:	5000MΩ min.	
DIELECTRIC WITHSTANDING VOLTAGE:	1000V AC rms	

			SW REFERENCE NO.: 630 COMBO ASSEMBLY			
		DRAWN: C.B	DATE: JAN. 01/20	19		
		CHECKED:	DATE:			
EDAC INC	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INCAND	SCALE: (IN C.A.D. 1:1)	SHEET 1 OF	2		
TORONTO, ONTARIO CANADA	SHALL NOT BE REPRODUCED, OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	DRAWING NUMBER: 630-5W1-640-1TE		ISSUE		
YOUR CONNECTION TO QUALITY & SERVICE		PART NUMBER: 630-5W1-	-640-1TE	1		





THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.

	THESE DRAWINGS AND SPECIF
NC	ARE THE PROPERTY OF EDAC
NTARIO	SHALL NOT BE REPRODUCED,O
A	OR USED AS THE BASIS FOR TH
	MANUFACTURE OR SALE OF AF
ERVICE	WITHOUT WRITTEN PERMISSIO

V REFERENCE NO .:	630 COMBO ASSEMBLY
AWN: C.B	DATE: JAN. 01/20
IECKED:	DATE:

