

NOTES: UNLESS OTHERWISE SPECIFIED

1. MATERIAL:

HOUSING: THERMOPLASTIC; BLACK SEAL: SILICONE RUBBER

2. MODIFICATIONS: BACKSHELL RING ADAPTER (BRA); REDUCED DIA. WIRE SEAL


- 3. SPECIFICATIONS:
 - 3.1 OPERATING TEMPERATURE: -55°C TO +125°C.
 - 3.2 DIELECTRIC WITHSTANDING VOLTAGE: LESS THAN 2 MILLIAMPS CURRENT LEAKAGE @ 1500 VOLTS AC.
 - 3.3 INSULATION RESISTANCE: 1000 MEGOHM MIN @ 25°C.
 - 3.4 MOISTURE RESISTANCE:

IP68(IM OF WATER FOR A PERIOD OF 24 HOURS, MATED CONDITION);

- IP69K(MATED CONDITION).
- 3.5 MATING CYCLE DURABILITY: 100 CYCLES
- 3.6 RoHS COMPLIANT
- 4. MATING PART: AHDP02-18-14P* & AHDP04-18-14P* (* = SEAL TYPE)
- 5. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.



CONTACT	MIN. INSUL	MAX. INSUL	TYPICAL	CURRENT	
SIZE	O.D.	O.D.	WIRE RANGE	RATING	
16	1.35 mm (.053in)	3.05 mm (.120 in)	14-20 AWG (2.0-0.5mm²)	13 AMPS	



BACKSHELL RING ADAPTER - BLUE

	AHDP06-18-14SR-BRA			REF:HDP26-18-14SE-L017			
QUANTITY	PART NUMBER		2	DESCRIPTION			
		ı	MAT	ERI	ALS LIST		
UNLESS OTHERWISE SPECIFIED 1) All dimensions are in metric(mm). 2) Tolerances are as follows: 1 PL DEC ±0.30 2 PL DEC ±0.05 3) Note reference = X		SIGNATURES		DATE	Amphonol		
		DRAWN:	MILO	30/MAR/22	Amphenol		
		CHECKED:	SULLEN	31/MAR/22	Sine Systems - www.amphenol-sine.com		
		ENGINEER:			44724 Morley Drive		
MATERIAI SPECIFICA	TIONS:	APPROVAL:	TOMMY	01/APR/22	Clinton Township, MI 48036		
WEIGHT: 48.3g		CUSTOMER:			14POS, PLUG, SOCKET, SIZE 18, RD SEAL, BRA, DURAMATE AHDP		
		SHOWN HEREON ARE THE PROPERTY OF THE AMPHENOL CORPORATION. NO RIGHTS OF REPRODUCTION ARE IMPLIED. ALL DIMENSIONS ARE SUBJECT TO NORMAL					
PROCESS SPECIFICATIONS:				ORMANCE DATA ROPERTY OF ON. NO RIGHTS LIED. ALL	B C- AHDP06-18-14SR-BRA	A1	
NEXT ASS'Y:		MANUFACTURING VARIATIONS.			SCALE: NONE DURAMATE SHEET 1 C	F 1	

AMATE AHDP