Product data sheet Characteristics

TMC4AI2

Analogue input cartridge, Modicon M241, 2 analog current inputs





Main

Range of Product	Modicon M241
Product or Component Type	Analogue input cartridge
Product Compatibility	Modicon M241C
Analogue input number	2

Complementary

Analogue input type	Current 420 mA Current 020 mA
	Voltage 010 V
Analogue input resolution	16 bits
LSB value	1 mV voltage
	2 μA current
Sampling duration	10 ms
Absolute accuracy error	+/- 0.2 % of full scale 77 °F (25 °C)
Temperature Drift	+/- 0.006 %FS/°C
Repeat accuracy	+/- 0.2 %FS
Non-linearity	+/- 0.05 %FS
Cross talk	80 dB
Type of Cable	Twisted shielded pairs cable
Electrical connection	1 x 1.5 mm ² 1 spring terminal block pitch 3.81 mm for inputs and supply
Maximum cable distance between devices	Twisted shielded pairs cable <98.43 ft (30 m) input
Insulation	Between input and internal logic 500 V DC
	Non-insulated between inputs
Supply voltage limits	20.428.8 V
Local signalling	For PWR 1 LED (green)
Height	1.97 in (50 mm)
Depth	0.83 in (21 mm)
Width	1.34 in (34 mm)
Net Weight	0.12 lb(US) (0.055 kg)
Permissible continuous overload	40 mA current
	30 V voltage
Input impedance	<= 250 Ohm current
	>= 1 MOhm voltage

Environment

ZIIVII OIIII OIIC		
Immunity to microbreaks	10 ms	

Ordering and shipping details

Category	22533-M2XX PLC & ACCESSORIES
Discount Schedule	MSX
GTIN	3606480649165
Nbr. of units in pkg.	1
Package weight(Lbs)	2.61 oz (74.0 g)
Returnability	Yes
Country of origin	ID

Packing Units

PCE
2.76 in (7 cm)
1.38 in (3.5 cm)
1.18 in (3 cm)
S02
27
4.94 lb(US) (2.24 kg)
5.91 in (15 cm)
11.81 in (30 cm)
15.75 in (40 cm)
PAL
69
9.66 lb(US) (4.382 kg)
40.00 in (101.6 cm)
36.00 in (91.44 cm)
48.00 in (121.92 cm)

Offer Sustainability

Sustainable offer status	Green Premium product	
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
REACh Regulation	[™] REACh Declaration	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	₫Yes	
China RoHS Regulation	☑ China RoHS Declaration	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	End Of Life Information	
PVC free	Yes	