

R53BR43905000K

Aliases (53BR43905000K)

R53B, Film, Metallized Polypropylene, Automotive Safety, 3.9 uF, 10%, 350 VAC (X2), 800 VDC, 125°C, Lead Spacing = 27.5mm



Click here for the 3D model.

Dimensions	
L	32mm +0.5/-0.7mm
Н	37mm +0.3/-0.7mm
т	22mm +0.3/-0.7mm
S	27.5mm +/-0.4mm
LL	25mm +2/-1mm
F	0.8mm +/-0.05mm

Packaging Specifications		
Packaging	Pizza, Box	
Packaging Quantity	112	

General Information			
Series	R53B		
Dielectric	Metallized Polypropylene		
Style	Radial		
Features	Automotive Grade, EMI Safety		
RoHS	Yes		
Lead	Wire Leads		
Safety Class	X2		
Qualifications	ENEC, UL, cUL, CQC, AEC-Q200		
AEC-Q200	Yes		
THB Performance	Yes		
Component Weight	32.4 g		
Construction	Parallel		

Specifications		
Capacitance	3.9 uF	
Capacitance Tolerance	10%	
Voltage AC	350 VAC (X2)	
Voltage DC	800 VDC	
Temperature Range	-40/+125°C	
Rated Temperature	125°C	
Dissipation Factor	0.3% 1KHz	
Insulation Resistance	2.5641 GOhms	
Max dV/dt	150 V/us	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.