


Recommended PCB Layout
(Top View)



Part Number	Color	Packaging	
STX-3500-3NTR	Black	Tape and Reel	
STX-3500-3N-701CTR	Pink	Tape and Reel	
STX-3500-3N-284CTR	Blue	Tape and Reel	
STX-3500-3N-577CTR	Green	Tape and Reel	
STX-3500-3N-235CTR	Burgundy	Tape and Reel	Discontinued

Materials and Finish

Housing: High Temp Thermoplastic
UL 94V-0 rated, Black Color,

Terminals: Copper alloy,
Silver plating all over
Nickel underplating

Electrical Characteristics

Contact Resistance:

Before Test:

50 milliohms max.

After Durability Test:

100 milliohms max.

Rated Voltage:

16 V DC

Rated Current:

0.3A

Insulation Resistance:

100 Megohms min.
at 500V DC

Dielectric Strength:

500V AC RMS for 1 minute

Mechanical Characteristics

Insertion Force:

3.0kg max.

Extraction Force:

0.2kg min.

Operating Temp:

-25°C to +85°C

Durability: 5000 mating cycles

RoHS COMPLIANT



Tolerances
X.X ± 0.25
X.XX ± 0.15
Unless Stated Otherwise

REV.	DATE	DESCRIPTION	REV. BY	CHK. BY	DRAWN BY	DATE
A2	01/24/08	Add Color Options	Will H.	H. MA		
A3	08/13/08	ECO #08-066	S. Vien	H. MA	R. Aguirre	07/14/05
A4	08/16/13	ECO #13-060	D. Gih	P. DalCanto		
A5	09/26/13	ECO #13-072	W. Cook	H. MA		
A6	07/16/15	ECO #15-034	H. MA	W. Cook		
A7	02/26/18	ECO #18-010	C. Kelleher	C. Kelleher		

STX-3500-3N

Stereo Jack, 3 Position, RoHS Compliant

All Plastic Body, Right Angle, SMT Type

