

- 1
- 2
- 3
- 4
- 5
- 6
- 7
- 8
- 9
- 10
- 11
- 12
- 13
- 14
- 15
- 16
- 17
- 18

MATERIAL

AISI 304 stainless steel.


FEATURES AND APPLICATIONS

PCM-SP distance plates are a useful accessory for the hinges CFM. / CMM. / CMM-SST / CMMY. , when sheet thickness differences or gaskets could cause mounting surfaces not on the same plane between the frame and door.

Value to compensate	Plate thickness h
1.0	1
1.5	1.5
2.0	1 + 1
2.5	1 + 1.5
3.0	3
4.0	3 + 1
4.5	3 + 1.5
5.0	5
6.0	3 + 3
6.5	5 + 1.5
8.0	5 + 3
10.0	5 + 5




The table also includes values to compensate requiring the use of two overlapping plates.



Conversion Table
1 mm = 0.039 inch

mm	inch
30	1.18
40	1.57
50	1.97
60	2.36



METRIC

Code	Description	L	B	d	f	f1	f2	h	b1	⚖️
429106	PCM-SP-SST-30-1	30	30	4	18	18	6	1	10.8	2
429101	PCM-SP-SST-30-1,5	30	30	4	18	18	6	1.5	10.8	3
429111	PCM-SP-SST-30-3	30	30	4	18	18	6	3	10.8	6
429116	PCM-SP-SST-30-5	30	30	4	18	18	6	5	10.8	10
429126	PCM-SP-SST-40-1	40	40	5	25	25	7.5	1	14.5	4
429121	PCM-SP-SST-40-1,5	40	40	5	25	25	7.5	1.5	14.5	6
429131	PCM-SP-SST-40-3	40	40	5	25	25	7.5	3	14.5	12
429136	PCM-SP-SST-40-5	40	40	5	25	25	7.5	5	14.5	20
429146	PCM-SP-SST-50-1	50	50	6	30	30	10	1	18	6
429141	PCM-SP-SST-50-1,5	50	50	6	30	30	10	1.5	18	10
429151	PCM-SP-SST-50-3	50	50	6	30	30	10	3	18	19
429156	PCM-SP-SST-50-5	50	50	6	30	30	10	5	18	30
429166	PCM-SP-SST-60-1	60	60	8	36	36	12.5	1	21.5	9
429161	PCM-SP-SST-60-1,5	60	60	8	36	36	12.5	1.5	21.5	14
429171	PCM-SP-SST-60-3	60	60	8	36	36	12.5	3	21.5	27
429176	PCM-SP-SST-60-5	60	60	8	36	36	12.5	5	21.5	44

Hinges and accessories