


## **Z0402C121ESMST**

Aliases (Z0402C121ESMST) Obsolete KEMET, Z-SMS, Ferrite Beads, Noise Suppression, 240 mOhms



General Information		
Series	Z-SMS	
Style	SMD Chip	
Description	Chip Bead Signal Line	
Features	The Best Material In The Z-SMS Series To Suppress The XL Component And Stop The Reduction Of The Wave-Form Integrity While Maintaining Attenuation In The High Frequency Area	
RoHS	Yes	

Specifications			
Impedance	120 Ohms (100 MHz)		
Impedance Tolerance	25%		
Ripple Current	450 mA (MAX)		
Temperature Range	-55/+125°C		

Click here for the 3D model.

Dimensions	/
Chip Size	0402
L	1mm +/-0.05mm
W	0.5mm +/-0.05mm
Т	0.5mm +/-0.05mm
В	0.25mm +/-0.1mm

Packaging Specifications			
Packaging	T&R		
Packaging Quantity	10000		

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.