



### Main

|                                    |  |
|------------------------------------|--|
| Range of Product                   | Telemecanique Cabling components   |
| Accessory / separate part category | Cabling accessories  |
| Accessory / Separate Part Type     | Connector  |
| Electrical connection              | Straight male connector M12, 5 pins  |
| Collar material                    | Metal  |
| Status LED                         | Without  |
| Cable connection                   | Spring 0.00 in <sup>2</sup> (0.5 mm <sup>2</sup> ) 0.16...0.31 in (4...8 mm) |

### Complementary

|                                |                       |
|--------------------------------|-----------------------|
| Cable connector fixing         | Screw-on              |
| [Ue] rated operational voltage | 30 V AC<br>36 V DC    |
| Line Rated Current             | 4 A                   |
| Enclosure Material             | Metal                 |
| Minimum insulating resistance  | 1000 GΩ               |
| Contact resistance             | 8000 μOhm             |
| Net Weight                     | 0.04 lb(US) (0.02 kg) |

### Environment

|                                       |                            |
|---------------------------------------|----------------------------|
| IP Degree of Protection               | IP67                       |
| Ambient Air Temperature for Operation | -40...185 °F (-40...85 °C) |

### Ordering and shipping details

|                       |                      |
|-----------------------|----------------------|
| Category              | 22483-MACHINE CABLES |
| Discount Schedule     | DS3                  |
| GTIN                  | 3389119053181        |
| Nbr. of units in pkg. | 1                    |
| Package weight(Lbs)   | 1.34 oz (38.0 g)     |
| Returnability         | No                   |
| Country of origin     | DE                   |

### Packing Units

|                              |                        |
|------------------------------|------------------------|
| Unit Type of Package 1       | PCE                    |
| Package 1 Height             | 0.79 in (2 cm)         |
| Package 1 width              | 1.38 in (3.5 cm)       |
| Package 1 Length             | 1.97 in (5 cm)         |
| Unit Type of Package 2       | S02                    |
| Number of Units in Package 2 | 100                    |
| Package 2 Weight             | 9.04 lb(US) (4.099 kg) |
| Package 2 Height             | 5.91 in (15 cm)        |
| Package 2 width              | 11.81 in (30 cm)       |
| Package 2 Length             | 15.75 in (40 cm)       |


## Offer Sustainability

|                            |   |
|----------------------------|---|
| California proposition 65  | WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |
| REACH Regulation           | <a href="#">REACH Declaration</a>   |
| REACH free of SVHC         | Yes   |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>  |
| Toxic heavy metal free     | Yes   |
| Mercury free               | Yes   |
| RoHS exemption information | <a href="#">Yes</a>   |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

Dimensions



(1) Cable gland : no. 7 plastic (Pg 7)

---

## Connections and Schemes

---

