THIS IS A C.A.D. GENERATED DRAWING DO NOT MAKE MANUAL REVISIONS TO MASTER.



ISSUE NUMBER

ORIGINAL

MATERIALS:

HOUSING: PBT, UL94V-0

SPECIFICATIONS

RATED VOLTAGE: 300V

RATED CURRENT: 12A MAX WITHSTAND VOLTAGE: AC1700V R.M.S.


CONTACT RESISTANCE: 10 mOHMS 4. MAX


5. **INSULATION RESISTANCE:**


1000 MOHMS MIN/DC 500V TEMPERATURE RANGE: -40°C ~ +105°C 6.


WATERPROOF GRADE: TESTED AND

CERTIFIED TO IP67









Waterproof Connector, Receptacle
568-001-000-200



EDAC INC TORONTO, ONTARIO

CANADA

YOUR CONNECTION TO QUALITY & SERVICE

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC., AND SHALL NOT BE REPRODUCED,OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

ACAD REFERENCE NO.	568-001-000-200
DRAWN:R.STA.MONICA	DATE: OCT.22/10
CHECKED:	DATE:
SCALE: NOT TO SCALE	SHEET 1 OF 1
DRAWING NUMBER	ISSUE

568-001-000-200



THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2002/95/EC AND 2002/96/EC FOR RoHS COMPLIANCY