

工	G	нт – – – – – – – – – – – – – – – – – – –	m	0







LAYOUT SHOWN AS

Keying Shown as example

CHARACTERISTICS

ယ

 \sim

-Mass

BASIC SERIES:

SHELL SIZE : 21

Н

SHELL TYPE : Square Flange Receptacle

CONTACT TYPE : Standard Crimp Contact

PLATING : W = Olive drab Cadmium

-Standard : Based on MIL-DTL-38999 Series III

1	-Shell Material	: Aluminium			
	-Shell Plating	: Olive drab Cadmium			
	-Insulator	: Thermoplastic			
	-Contacts	: Copper Alloy			
	-Seals & Grommet	: Silicon Elastomer			
	-Contact Plating	: Gold over copper Alloy 0.8µm minimum			
	-Durability	: 500 Mating cycles			
	-Delivered with Souriau contacts and Accessories				
	-Temperature Range	: -65℃ to +175℃			
	-Salt Spray	: 500 hours			

: 59.15 g ± 10%

8D 0

G

21

W

11

S

F

D


Connector dimension			
Dim	Nominal		
Р	3.25±0.2		
PP	4.93±0.2		
R1	31.75		
R2	29.36		
S	39.7±0.3		
V	20.07+0/-1.25		
W	2.1/3.2		
Z	31.5 Max		
VV THREAD	M31x1-6g		

ORIENTATION : D

CONTACT LAYOUT : 21-11

CONTACT TYPE : SOCKET(500 Matings)

Е





	ω		А			
-						
					4	
1	6 50					
	A DENSES	7				
	1000					
	11.20					
		15				
S EXA	AMPLE				3	
anv	non-conformit	ty or damage				
s whic	ch does not co he Parties or b	mply with	1			
	on, technical n		- y			
untry	Jurisd	liction & Cont	rol List]		
R		Not Listed			2	
1W11SD						
		CUSTOME	R DRAWING	MOD N°		
um	n Receptacle 8D series					
ar	NPRDS / PROJECT					
			59		4	
This document is the property of SOURIAU					1	
J.CC	COM it must not be reproduced or communicated without permission					
	U DRG N° SHEET					
	1SD-C			1/2		
	В		А		ı	

		<mark>۵</mark>	г П	m	D	0
		Contact Layout				Panel Cutou
4	-x ($\begin{array}{c} c & +Y \\ & & \\ & & \\ & & \\ & \\ & \\ & \\ & \\ & $				SQUARE FLANGE RECEPTACLE (TYPE 0) REAR MOUNTING
	B +:306 (7.77) C +:348 (8.84) D +:227 (5.77) E +:000 (0.00) F -:227 (5.77) Shell Arrangement no. Nu <col/> cc <licc< li=""></licc<>	Contacts (Insert arrangement 21-11) on Contact Y-axis Location y-axis position X-axis Y-axis (mm) (mm) ID (mm) (mm) +332 (8.43) G -348 (8.84) -061 (1.55) +177 (4.50) H -306 (7.77) +177 (4.50) -206 (6.86) K +000 (0.00) +123 (3.12) -353 (8.97) L +.000 (0.00) -115 (2.92) -270 (6.86) mber of ntacts Size Service Contact Supersed location 11 12 I All MS20055-	5			ØA
S	21 -11	11 12 1 All MS20039-	-			Dim ØA ØAA R1 ØT
	_					
	~					SOURIAU shall not be liable for any due to a use of the Products whi the Specifications issued by either of (professional recommendati
N						Country FR
						PN: 8D021W
						-2016 First Release
					ISS DA Designed By:	ATE Latest modification - by Date:
					TITLE	
_					SCALE NA	General linear Tolerances:
					SOURI	AU WWW.SOURIAU.C
					FORMAT A3	SOURIAU 8D021W
	Н	G	F	E	D	C

