



(1.50 MAX)
(WITH MAXIMUM CARD)



NOTES:

1. MATERIALS:
 - 1.1 CONNECTOR:-
 - INSERT MOLD HOUSING: LCP, GLASS FILLED, UL94V-0, COLOUR BLACK.
 - TERMINAL: TITANIUM COPPER, THICKNESS: 0.12MM
 - DETECT PIN: TITANIUM COPPER, THICKNESS: 0.12MM
 - SHELL: STAINLESS STEEL, THICKNESS: 0.10MM
 2. PLATING FINISHES:
 - 2.1 TERMINAL:-
 - CONTACT: 0.38um MIN. GOLD ON CONTACT AREA OVER 2.00um MIN. NICKEL UNDERPLATE.
 - SOLDERTAIL: 0.025um MIN. GOLD FLASH OVER 2.00um MIN. NICKEL UNDERPLATE.
 - 2.2 SHELL:-
 - CONTACT: 0.05um MIN. GOLD ON CONTACT AREA OVER 2.00um MIN. NICKEL UNDERPLATE.
 - SOLDERTAIL: 0.025um MIN. GOLD FLASH OVER 2.00um MIN. NICKEL UNDERPLATE.
 - 2.3 DETECT PIN:-
 - CONTACT: 0.127um MIN. GOLD ON CONTACT AREA OVER 2.00um MIN. NICKEL UNDERPLATE.
 - SOLDERTAIL: 1.27um MIN. MATTE TIN OVER 2.00um MIN. NICKEL UNDERPLATE.
 3. PRODUCT SPECIFICATION: PS-151073-0001
 4. PACKAGING SPECIFICATION: PK-151073-0001
 5. OVERALL (SOLDERTAIL & SOLDERTAB) COPLANARITY 0.08MM MAX. BEFORE REFLOW.
 6. CONNECTOR TO BE USED TOGETHER WITH MOLEX NANO SIM CARD TRAY ONLY.
- △ DIMENSION INCLUSIVE OF BULGE


THIS DESIGN IS BASED ON DESIGN OBJECTIVES AND IS STRICTLY TENTATIVE. IT MAY CHANGE BASED ON RESULTS OF ADDITIONAL DESIGN REVIEWS & VERIFICATIONS.




CHANGE DECIMAL SHEETS EC NO: S2016-0055 DRWN: SCHEONG CHKD: GMENARLY APPR: KHL IM	REV 13	DESCRIPTION QUALITY SYMBOLS F _A =0 F _C =0 F _P =0	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE MM ONLY		SCALE NTS	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION	
				mm	INCH	DRAWN BY SCHEONG	DATE 2014/07/16	TITLE NANO SIM CONNECTOR 1.32MM HEIGHT WITH TRAY AND DETECT PIN		
			4 PLACES	± 0.100	± ---	CHECKED BY GMENARLY	DATE 2015/03/10	molex		
			3 PLACES	± ---	± ---	APPROVED BY KHL IM	DATE 2015/03/12			
ANGULAR ± 3 °		DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		MATERIAL NO. SEE TABLE		DOCUMENT NO. SD-151073-0001		SHEET NO. 1 OF 3		
THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION										

10 9 8 7 6 5 4 3 2 1

CENTRELINES OF TRAY AND CONNECTOR OPENING ARE THE SAME



CONNECTOR WITH TRAY




SYSTEM LEVEL

DESCRIPTION	PART NUMBER
CONNECTOR	151073-1000
NANO SIM CARD TRAY	151073-0011 (WITHOUT RETENTION FEATURES)
	151073-0030 (WITH RETENTION FEATURES)

CARD INSERTION STATE	DETECT SWITCH CIRCUIT STATE	SCHEMATIC
CARD MATED	OPENED	
CARD UNMATED	CLOSED	

CHANGE DECIMAL SHEETS EC NO: S2016-0055 DRWN: SCHEONG 2015/07/01 CHKD: GMENARLY 2015/07/30 APPR: KHL IM 2015/08/05	QUALITY SYMBOLS	GENERAL TOLERANCES (UNLESS SPECIFIED)	DIMENSION STYLE	SCALE	DESIGN UNITS	THIRD ANGLE PROJECTION
	$F_A=0$	mm INCH	MM ONLY	NTS	METRIC	
	$F_G=0$	4 PLACES ± 0.100 ± ---	DRAWN BY DATE			TITLE
	$F_P=0$	3 PLACES ± --- ± ---	CHECKED BY DATE			NANO SIM CONNECTOR 1.32MM HEIGHT WITH TRAY AND DETECT PIN molex
		2 PLACES ± 0.10 ± ---	APPROVED BY DATE			
	1 PLACE ± --- ± ---	MATERIAL NO.	SEE TABLE		DOCUMENT NO.	SHEET NO.
	0 PLACE ± --- ± ---				SD-151073-0001	2 OF 3
	ANGULAR ± 3 °	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION			

9 8 7 6 5 4 3 2 1





RECOMMENDED PCB LAYOUT
PWB TOLERANCE : ±0.05MM


FOR REFERENCE ONLY

REVISED IEC NO: 5 DRWNS: SCHEONG CHKD: APPR:	QUALITY SYMBOLS $\nabla_F = 0$ $\nabla_E = 0$ $\nabla_D = 0$	GENERAL TOLERANCES (UNLESS SPECIFIED) <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th></th> <th>mm</th> <th>INCH</th> </tr> </thead> <tbody> <tr> <td>4 PLACES</td> <td>± ---</td> <td>± ---</td> </tr> <tr> <td>3 PLACES</td> <td>± ---</td> <td>± ---</td> </tr> <tr> <td>2 PLACES</td> <td>± 0.20</td> <td>± ---</td> </tr> <tr> <td>1 PLACE</td> <td>± ---</td> <td>± ---</td> </tr> <tr> <td>0 PLACE</td> <td>±</td> <td>±</td> </tr> </tbody> </table>		mm	INCH	4 PLACES	± ---	± ---	3 PLACES	± ---	± ---	2 PLACES	± 0.20	± ---	1 PLACE	± ---	± ---	0 PLACE	±	±	DIMENSION STYLE MM ONLY	SCALE NTS	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION
		mm	INCH																					
	4 PLACES	± ---	± ---																					
	3 PLACES	± ---	± ---																					
2 PLACES	± 0.20	± ---																						
1 PLACE	± ---	± ---																						
0 PLACE	±	±																						
REV: 5	DESCRIPTION	ANGULAR ± 3 ° DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	DRAWN BY: SCHEONG DATE: 2014/05/21 CHECKED BY: DATE: APPROVED BY: DATE:	TITLE SALES DRAWING MICRO SIM CONNECTOR 1.45MM HEIGHT, PUSH PULL																				
			MATERIAL NO. 151070-0001	DOCUMENT NO. SD-151070-0001																				
			SIZE A3	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION																				


PACKAGING INFORMATION



NOTES :
1. LEADER & TRAILER TAPE



2. PEELING OFF FORCE OF THE TOP TAPE : 20-80gf.
(PEELING DIRECTION AS SHOWN IN THE FOLLOWING FIGURE)



3. TAPE & REEL SPECIFICATION IS AS PER EIA-481.
4. TAPE & REEL QTY. : 1500PCS / REEL.
5. THE TAPE IS TREATED FOR ANTI-STATIC.

REVISED IEC NO: S2015-0253 DRW: SCHEONG 2014/10/09 CHKD: APPR:	QUALITY SYMBOLS	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE	SCALE	DESIGN UNITS	THIRD ANGLE PROJECTION	
	$\nabla_F = 0$	mm	INCH	MM ONLY	NTS	METRIC		
	$\nabla_E = 0$	4 PLACES ± --- ± ---	3 PLACES ± --- ± ---	2 PLACES ± 0.20 ± ---	1 PLACE ± --- ± ---	0 PLACE ± ±	SALES DRAWING MICRO SIM CONNECTOR 1.45MM HEIGHT, PUSH PULL	
	$\nabla_B = 0$	ANGULAR ± 3°		DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		molex MATERIAL NO. 151070-0001 DOCUMENT NO. SD-151070-0001 SHEET NO. 3 OF 3		
REV	DESCRIPTION	SIZE A3		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION				