



LAYOUT SHOWN AS EXAMPLE

Keying Shown as example

**CHARACTERISTICS**

- Standard : Based on MIL-DTL-38999 Series III
- Shell Material : Composite
- Shell Plating : Olive drab Cadmium
- Insulator : Thermoplastic
- Contacts : Copper Alloy
- Seals & Grommet : Silicon Elastomer
- Contact Plating : Gold over copper Alloy 0.8µm minimum
- Durability : 500 Mating cycles
- Delivered with Souriau contacts and Accessories
- Temperature Range : -65°C to +175°C
- Salt Spray : 2000 hours

| Connector dimension |             |
|---------------------|-------------|
| Dim                 | Nominal     |
| P                   | 3.25±0.2    |
| PP                  | 4.93±0.2    |
| R1                  | 29.36       |
| R2                  | 26.97       |
| S                   | 36.5±0.3    |
| V'                  | 19.5+1.4/-0 |
| W'                  | 2.1/3.65    |
| Z'                  | 32 Max      |
| VV THREAD           | M28x1-6g    |

SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)

|         |                             |
|---------|-----------------------------|
| Country | Jurisdiction & Control List |
| FR      | Not Listed                  |

**PN: 8D019J18BC**

|   |                                    |                                |                               |
|---|------------------------------------|--------------------------------|-------------------------------|
| A   | 08-10-2016                         | First Release                  |                               |
| ISS   | DATE                               | Latest modification - by       | MOD N°                        |
| Designed By:  |                                    | Date:                          | <b>CUSTOMER DRAWING</b>       |
| <b>TITLE</b>  |                                    | Composite Receptacle 8D series |                               |
| SCALE   | NA                                 | General linear Tolerances: ±-- | NPRDS / PROJECT<br><b>859</b> |
| <b>SOURIAU</b>  |                                    | <b>WWW.SOURIAU.COM</b>         |                               |
| This document is the property of SOURIAU it must not be reproduced or communicated without permission |                                    |                                |                               |
| FORMAT  | <b>SOURIAU DRG N° 8D019J18BC-C</b> |                                | SHEET<br>1/2                  |

|                |                                    |   |   |    |   |    |   |   |                 |
|----------------|------------------------------------|---|---|----|---|----|---|---|-----------------|
| BASIC SERIES:  | 8D                                 | 0 | - | 19 | J | 18 | B | C | ORIENTATION : C |
| SHELL TYPE :   | Square Flange Receptacle           |   |   |    |   |    |   |   |                 |
| CONTACT TYPE : | Standard Crimp Contact             |   |   |    |   |    |   |   |                 |
| SHELL SIZE :   | 19                                 |   |   |    |   |    |   |   |                 |
| PLATING :      | J = Olive drab Cadmium             |   |   |    |   |    |   |   |                 |
|                | CONTACT TYPE : SOCKET(500 Matings) |   |   |    |   |    |   |   |                 |
|                | CONTACT LAYOUT : 19-18             |   |   |    |   |    |   |   |                 |

Contact Layout



(Inactive for new design for MIL-DTL-38999. For new design, use arrangement no. 19-19.)

| Contacts<br>(Insert arrangement 19-18) |             |             |                     |             |             |                  |
|--|-------------|-------------|---------------------|-------------|-------------|------------------|
| Contact position ID                    | Location    |             | Contact position ID | Location    |             | Standard contact |
|  | X-axis (mm) | Y-axis (mm) |                     | X-axis (mm) | Y-axis (mm) |                  |
| A                                      | +068 (1.73) | +380 (9.65) | K                   | -180 (4.57) | -180 (4.57) | M39029/90-529    |
| B                                      | +180 (4.57) | +180 (4.57) | L                   | -377 (9.58) | -065 (1.65) |                  |
| C                                      | +377 (9.58) | +065 (1.65) | M                   | -317 (8.05) | +000 (0.00) | M39029/58        |
| D                                      | +317 (8.05) | +000 (0.00) | N                   | -377 (9.58) | +065 (1.65) |                  |
| E                                      | +377 (9.58) | -065 (1.65) | P                   | -180 (4.57) | +180 (4.57) | M39029/91-530    |
| F                                      | +180 (4.57) | -180 (4.57) | R                   | -068 (1.73) | +380 (9.65) |                  |
| G                                      | +068 (1.73) | -380 (9.65) | S                   | +000 (0.00) | +319 (8.10) | M39029/56        |
| H                                      | +000 (0.00) | -319 (8.10) | T                   | +000 (0.00) | +044 (1.12) |                  |
| J                                      | -068 (1.73) | -380 (9.65) | U                   | +000 (0.00) | -044 (1.12) |                  |

  

| Shell size | Arrangement No. | Number of contacts | Size contacts | Service rating | Contact location | Standard contact |               |
|------------|-----------------|--------------------|---------------|----------------|------------------|------------------|---------------|
|            |                 |                    |               |                |                  | Pin              | Socket        |
| 19         | 18              | 4                  | 8 (see note)  | Twinax         | B, F, K, P       | M39029/90-529    | M39029/91-530 |
|            |                 | 14                 | 22D           | M              | All others       | M39029/58        | M39029/56     |

Panel Cutout



| Dim | Nominal    |
|-----|------------|
| ØA  | 32.96 min  |
| ØAA | 28.98 min  |
| R1  | 29.36      |
| ØT  | 3.25 ±0.13 |

SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)

| Country | Jurisdiction & Control List |
|---------|-----------------------------|
| FR      | Not Listed                  |

**PN: 8D019J18BC**

|                |                                       |                                |   |
|----------------|---------------------------------------|--------------------------------|---|
| A              | 08-10-2016                            | First Release                  |   |
| ISS            | DATE                                  | Latest modification - by       | MOD N°  |
| Designed By:   |                                       | Date:                          | <b>CUSTOMER DRAWING</b>   |
| <b>TITLE</b>   | <b>Composite Receptacle 8D series</b> |                                |   |
| SCALE          |                                       | General linear Tolerances: ±-- | NPRDS / PROJECT<br><b>859</b>   |
| NA             |                                       |                                |   |
| <b>SOURIAU</b> | <b>WWW.SOURIAU.COM</b>                |                                | This document is the property of SOURIAU it must not be reproduced or communicated without permission |
| FORMAT         | <b>SOURIAU DRG N° 8D019J18BC-C</b>    |                                | SHEET<br>2/2  |