

CnC Tech

Product change note:

FLAT Ribbon Cables:

MULTI-COLOR FLAT RIBBON CABLE:

304-28-XX-MC-XXXXF

Changes:

<u>D/C prior to 19/43</u>	<u>after D/C 19/43</u>
CoO: CHINA	TAIWAN
UL2651	UL20029
Conductor Diameter: 0.381mm	0.39mm +/-0.05mm
Diameter: 0.9mm +/- 0.1mm	0.9mm +/- 0.05mm
Spark Test: -	3000V/0.15 Sec. Min.
Insulation Resistance: 100MΩ/Km 20°C	75MΩ/Km 20°C
<u>General Tolerance:</u>	
.X = +/- 0.3	.X = +/- 0.2
.XX = +/- 0.15	.XX = +/- 0.15

GRAY FLAT RIBBON CABLE

302-28-XX-GR-XXXXF

Changes:

<u>D/C prior to 19/36</u>	<u>after D/C 19/36</u>
CoO: CHINA	TAIWAN
Construction: 7/0.12 +/-0.003mm	7/0.127 +/-0.005mm
Conductor Diameter: 0.36mm	0.39mm +/-0.05mm
Min Thickness: 0.23mm	7mil
E Marking: E332441	E315658
Insulation Resistance: 100MΩ/Km 20°C	100MΩ/Km 20°C
<u>General Tolerance:</u>	
.X = +/- 0.2	.X = +/- 0.2
.XX = +/- 0.25	.XX = +/- 0.15

CnC Tech

GRAY FLAT RIBBON CABLE

300-30-XX-GR-XXXXF

Changes:

<u>D/C prior to 19/36</u>	<u>after D/C 19/36</u>
CoO: CHINA	TAIWAN
Construction: 7/0.1 +/-0.005mm	7/0.1 +/-0.005mm
Conductor Diameter: 0.36mm	0.3mm +/-0.05mm
Material: PVC	PVC
Min Thickness: 0.15mm	6 mil
Max Thickness: 0.18mm	-
Average Thickness: -	7 mil
Diameter: 0.66 +/- 0.08mm	0.66 +/- 0.05mm
E Marking: E332441	E315658
Cond. Resistance: 337Ω/Km 20°C	361 Ω/Km 20°C
Insulation Resistance: 100MΩ/Km 20°C	100MΩ/Km 20°C
<u>General Tolerance:</u>	
.X = +/- 0.3	.X = +/- 0.2
.XX = +/- 0.15	.XX = +/- 0.15