



LAYOUT SHOWN AS EXAMPLE

Keying Shown as example

**CHARACTERISTICS**

- Standard : Based on MIL-DTL-38999 Series III
- Shell Material : Aluminium
- Shell Plating : Black Zinc Nickel
- Insulator : Thermoplastic
- Contacts : Copper Alloy
- Seals & Grommet : Silicon Elastomer
- Contact Plating : Gold over copper Alloy 0.8µm minimum
- Durability : 500 Mating cycles
- Delivered with Souriau contacts and Accessories
- Temperature Range : -65°C to +175°C
- Salt Spray : 500 hours
- Mass : 112.83 g ± 10%

| Connector dimension |          |
|---------------------|----------|
| Dim                 | Nominal  |
| ØS                  | 48 Max   |
| Z                   | 31 Max   |
| VV THREAD           | M37x1-6g |

SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)

| Country | Jurisdiction & Control List |
|---------|-----------------------------|
| FR      | Not Listed                  |

**PN: 8D525Z08BE**

|              |   |                                |   |
|--------------|---|--------------------------------|---|
| A            | 17-10-2016  | First Release                  |   |
| ISS          | DATE  | Latest modification - by       | MOD N°  |
| Designed By: |   | Date:                          | <b>CUSTOMER DRAWING</b>   |
| <b>TITLE</b> | <b>Aluminium Plug 8D series</b>                                     |                                |   |
| SCALE        |   | General linear Tolerances: ±-- | NPRDS / PROJECT<br><b>859</b>   |
| NA           | <b>SOURIAU</b> <a href="http://WWW.SOURIAU.COM">WWW.SOURIAU.COM</a> |                                | This document is the property of SOURIAU it must not be reproduced or communicated without permission |
| FORMAT       | <b>A3</b>   |                                | <b>SOURIAU DRG N° 8D525Z08BE-C</b> SHEET 1/2  |

|                |                         |   |   |    |                                    |    |   |   |                 |
|----------------|-------------------------|---|---|----|------------------------------------|----|---|---|-----------------|
| BASIC SERIES:  | 8D                      | 5 | - | 25 | Z                                  | 08 | B | E | ORIENTATION : E |
| SHELL TYPE :   | Plug with RFI Shielding |   |   |    | CONTACT TYPE : SOCKET(500 Matings) |    |   |   |                 |
| CONTACT TYPE : | Standard Crimp Contact  |   |   |    | CONTACT LAYOUT : 25-08             |    |   |   |                 |
| SHELL SIZE :   | 25                      |   |   |    |                                    |    |   |   |                 |
| PLATING :      | Z = Black Zinc Nickel   |   |   |    |                                    |    |   |   |                 |

Contact Layout



Inactive for new design for MIL-DTL-38999. For new design, use arrangement no. 25-10.)

| Contact position ID | Contact location |              |
|---------------------|------------------|--------------|
|                     | X-axis (mm)      | Y-axis (mm)  |
| A                   | -000 (0.00)      | -426 (10.82) |
| B                   | +333 (8.46)      | +266 (6.76)  |
| C                   | +415 (10.54)     | -095 (2.41)  |
| D                   | +185 (4.70)      | -384 (9.75)  |
| E                   | -185 (4.70)      | -384 (9.75)  |
| F                   | -415 (10.54)     | -095 (2.41)  |
| G                   | -333 (8.46)      | +266 (6.76)  |
| H                   | +000 (0.00)      | +000 (0.00)  |

| Shell size | Arrangement no. | Number of contacts | Size contacts | Service rating | Contact location | Standard contact |               |
|------------|-----------------|--------------------|---------------|----------------|------------------|------------------|---------------|
|            |                 |                    |               |                |                  | Pin              | Socket        |
| 25         | -8              | 8                  | 8             | Twinax         | All              | M39029/90-529    | M39029/91-530 |

SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)

| Country | Jurisdiction & Control List |
|---------|-----------------------------|
| FR      | Not Listed                  |

PN: 8D525Z08BE

|                |                                    |                            |   |
|----------------|------------------------------------|----------------------------|---|
| A              | 17-10-2016                         | First Release              |   |
| ISS            | DATE                               | Latest modification - by   | MOD N°  |
| Designed By:   |                                    | Date:                      | <b>CUSTOMER DRAWING</b>   |
| <b>TITLE</b>   | Aluminium Plug 8D series           |                            |   |
| SCALE          |                                    | General linear Tolerances: | NPRDS / PROJECT   |
| NA             |                                    | ±--                        | <b>859</b>  |
| <b>SOURIAU</b> | <b>WWW.SOURIAU.COM</b>             |                            | This document is the property of SOURIAU it must not be reproduced or communicated without permission |
| FORMAT         | <b>SOURIAU DRG N° 8D525Z08BE-C</b> |                            | SHEET 2/2   |