

# GMA.1B.040.RN

## SUMMARY

#### # Wires



Image is for illustrative purpose only

| Series           | 1B                      |  |
|------------------|-------------------------|--|
| Termination type | No contacts / Accessory |  |
| IP rating        | 0                       |  |
| AWG wire size    | 0.00 - 0.00             |  |
| Cable Ø          | 4.00 - 4.40 mm          |  |
| Status           | active                  |  |

### Download

Request a quote Catalog

## **TECHNICAL DETAILS**

#### **Mechanics**

| GMA*: Bend relief Black |
|-------------------------|
| No keying               |
| Silicone elastomer VMQ  |
| N : Black               |
| .96 g                   |
|                         |

#### Performance


Configuration Insulator Rated Current

#### Others

Temp (min / max): -60°C / +200°C Temperature range in water steam: +140°C

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

### DRAWINGS



No keying

#### Dimensions

|     | А    | L    |
|-----|------|------|
| mm. | 4.0  | 34   |
| in. | 0,16 | 1,34 |

### **RECOMMENDED BY LEMO**

Tools

Cables

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.