

UNLESS O	TOLERANCE UNLESS OTHERWISE SPECIFIED			
.X	±0.25			
.XX	±0.13			
YYY	+0.05			

THIS IS A C.A.D. GENERATED DRAWING DO NOT MAKE MANUAL REVISIONS TO MASTER.



ISSUE NUMBER ORIGINAL





NOTES:

MATERIAL:

HOUSING: THERMOPLASTIC POLYESTER, UL94V-0

SHELL: STEEL, NICKEL PLATED

CONTACT: COPPER ALLOY, GOLD FLASH PLATED

OPERATING TEMPERATURE: -55°C ~ 125°C

POWER/CO-AX CONTACT RATING: 75Ω (IMPEDANCE)

(IF PRESENT)


SIGNAL CONTACT CURRENT RATING: 5A PER CONTACT


SIGNAL CONTACT RESISTANCE: $10m\Omega$ MAX.

INSULATOR RESISTANCE: 5000MΩ min.

DIELECTRIC

WITHSTANDING VOLTAGE: 1000V AC rms





COMBINATION D-SUB



EDAC INC TORONTO, ONTARIO CANADA

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC..AND SHALL NOT BE REPRODUCED, OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

	SW REFERENCE NO.: 629 COMBO ASSEMBLY			
	DRAWN: C.B	DATE: JAN. 01/2019		
	CHECKED:	DATE:		
	SCALE: (IN C.A.D. 1:1)	SHEET 1 OF 2		
ĺ	DD 444/14 0 444 14 14 15 15 16 16 16 16 16 16 16 16 16 16 16 16 16	240.7ND		

629-2W2-240-7ND ISSUE DRAWING NUMBER: PART NUMBER: 629-2W2-240-7ND

TOLERANCE UNLESS OTHERWISE SPECIFIED

.X ±0.25 .XX ±0.13 .XXX ±0.05

THIS IS A C.A.D. GENERATED DRAWING DO NOT MAKE MANUAL REVISIONS TO MASTER.



ISSUE NUMBER (1) ORIGINAL

00





2W2

2WK2

5W1









7W2

11W1



9W4




13W3





17W2












0000000

21W4











47W1

COMBINATION D-SUB



EDAC INC TORONTO, ONTARIO CANADA

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC..AND SHALL NOT BE REPRODUCED,OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

SW REFERENCE NO.:	REFERENCE NO.: 629 COMBO ASSEMBLY					
DRAWN: C.B		DATE:	JAN.	01/20	19	
CHECKED:		DATE:				
SCALE: N.T.S		SHEET	2	OF	2	
DRAWING NUMBER: 629-2W2-240-7ND		ISSU	JE			

629-2W2-240-7ND

PART NUMBER:

THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.

COMPLIANT