


NOTES: UNLESS OTHERWISE SPECIFIED

- P/N: 9205-HS  
INSULATOR: HEAT SHRINK TUBING 221. BLACK.  
BODY: BRASS. 40μ [1.02μm] MIN GOLD OVER NICKEL PLATED.  
CONTACT: BeCu OR PHOSPHOR BRONZE. 40μ [1.02μm] MIN GOLD OVER NICKEL PLATED.
- P/N: 9274COLOR  
INSULATOR: MOLDED PVC. AVAILABLE IN TEN COLORS.  
ALLIGATOR: STEEL. NICKEL PLATED.
- P/N: W-200/COLOR  
22AWG 65X40 TINNED COPPER  
0.070 [1.78] O.D. PVC INSULATION  
AVAILABLE IN TEN COLORS.
- PERFORMANCE  
MAXIMUM CURRENT: 2.5 AMPS  
MAXIMUM VOLTAGE: 1000 (300 UL) W.V.D.C.  
MAXIMUM TEMPERATURE: 221°F (105°C)



LTR	REVISIONS	DESCRIPTION	DATE	APPROVED

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ARE: FRACTIONS DECIMALS ANGLES		CONTRACT NO.		DESCRIPTION	
±	.XX ±	±	±	APPROVALS	DATE
±	.XXX ±	±	±	DRAWN	R.L. 10/10
MATERIAL SEE NOTE.		APPROVED BY		0.025 [0.64] SQ. SOCKET TO STD ALLIGATOR (9274)	
FINISH SEE NOTE.				SIZE CODE IDENT NO. DRAWING NO.	
USED ON				A 08505 9172	
APPLICATION		DO NOT SCALE DRAWING		SCALE 1:1	
				SHEET 1 OF 1	

**E-Z-HOOK** DIVISION OF TEKTEST INC. ARCADIA, CA 91006 U.S.A.

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-Z-HOOK. THE INFORMATION IS NOT TO BE REPRODUCED WITHOUT PRIOR WRITTEN PERMISSION OF E-Z-HOOK. DIV. OF TEKTEST INC. MAXIMUM TESTED RATINGS IN A HANDS-FREE CONTROLLED ENVIRONMENT. MAXIMUM RATINGS ARE NOT TO BE USED CONCURRENTLY.