

Electronic housing - HCS-C MAXI 1W 2X9V 1 1 7035 - 2203170

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Handheld housing, C-Maxi, light gray, consisting of two half shells, two front plates, screws. Front 1.1 mm recessed, with window and keypad slot, battery compartment cover and battery contacts for 2x 9 V battery

Your advantages

- ✔ Item is from the HCS product range
- ✔ Suitable for handheld devices
- ✔ Ergonomic straight or staggered housing design
- ✔ Integration of LCD displays and membrane keypads
- ✔ Degree of protection: up to IP54
- ✔ Temperature range: -20 °C to +50 °C
- ✔ Shock-resistant ABS plastic
- ✔ Flammability rating UL 94-V0

Key Commercial Data

Packing unit	1 pc
GTIN	
GTIN	4055626377261

Technical data

Item properties

Type	HCS-C MAXI 1W 2X9V 1 1 7035
Order No.	2203170
Housing type	Handheld housing
Type	straight
Battery compartment	2 x 9 V

Measurements

Caption	Schematic representation – for additional information, see product range drawing in the Download Center
---------	---

Electronic housing - HCS-C MAXI 1W 2X9V 1 1 7035 - 2203170

Technical data

Measurements

Width [w]	94 mm
Height [h]	182.5 mm
Depth [d]	39 mm
Diagonal	2.8 in. (Window for display)
Dimensions	73 mm x 80 mm x 1.1 mm (Recessed area on front)
	73 mm x 7.9 mm x 1.1 mm (Recessed area on front)
	73 mm x 8 mm x 1.1 mm (Recessed area on front)
	62 mm x 33 mm (Window for display)
Front with faceplate	top, 1 x (73.8 mm x 25.8 mm)
	bottom, 1 x (73.8 mm x 25.8 mm)

Material specifications

Color (RAL)	light gray (7035)
Flammability rating according to UL 94	V0
Housing material	ABS

Hammer test

Specification	IEC 60068-2-75:2014-09
Impact energy	0.7 J
Number of drop cycles	5

Thermostability (ball thrust test)

Specification	IEC 60695-10-2:2014-02
Temperature	80 °C
Test duration	1 h
Force	20

Test for assessing the risk of fire (glow wire)

Specification	IEC 60695-2-11:2014-02
Temperature	850 °C
Time of exposure	30 s

Packaging information

Pieces per package	1
Denomination packing units	Pcs.


Standards and regulations

Flammability rating according to UL 94	V0
--	----

Drawings

Electronic housing - HCS-C MAXI 1W 2X9V 1 1 7035 - 2203170

Dimensional drawing



Schematic representation – for additional information, see product range drawing in the Download Center

Phoenix Contact 2019 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>