

NOTES:

| MATERIAL: | |
|-----------|--|
| HOUSING: | |
| SHELL: | |
| CONTACT: | |
| | |

THERMOPLASTIC POLYESTER, UL94V-0 STEEL, TIN PLATED COPPER ALLOY, GOLD FLASH PLATED

OPERATING TEMPERATURE:

.XX ±0.13


.XXX ±0.05

POWER/CO-AX CONTACT RATING: 10A (CURRENT) (IF PRESENT) SIGNAL CONTACT CURRENT RATING: 5A PER CONTACT SIGNAL CONTACT RESISTANCE: $10m\Omega$ MAX. **INSULATOR RESISTANCE:** 5000MΩ min.


DIELECTRIC WITHSTANDING VOLTAGE:

-55°C ~ 125°C

1000V AC rms



| COMBINATION D-SUB | | SW REFERENCE NO.: 630 COMBO ASSEMBLY | | | | |
|--|--|--|--------------------------|--------------------|------------|-------|
| | | DRAWN: C.B | | DATE: JAN. 01/2019 | | |
| | | CHECKED: | | DATE: | | |
| EDAG INC TORONTO, ONTARIO CANADA YOUR CONNECTION TO QUALITY & SERVICE | | THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC.,AND SHALL NOT BE REPRODUCED,OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION. | SCALE: | (IN C.A.D. 1:1) | SHEET 1 OF | 2 |
| | | | DRAWING NUMBER: 630-17W2 | | 2250-1T2 | ISSUE |
| | | | PART NU | MBER: 630-17W2 | 2250-1T2 | 1 |



COMPLIANT

