
THIS IS A C.A.D. GENERATED DRAWING TOLERANCE UNLESS OTHERWISE SPECIFIED DO NOT MAKE MANUAL REVISIONS TO MASTER.

6.10

+ 11.00











THERMOPLASTIC POLYESTER, UL94V-0 STEEL, NICKEL PLATED COPPER ALLOY, GOLD FLASH PLATED




30A (CURRENT) POWER/CO-AX CONTACT RATING: (IF PRESENT) SIGNAL CONTACT CURRENT RATING: 5A PER CONTACT SIGNAL CONTACT RESISTANCE: $10m\Omega$ MAX.

5000MΩ min.



	COMBINATION D-SUB			SW REFERENCE NO.: 629 COMBO ASSEMBLY			
					DATE: JAN. 01/2	019	
			CHECKED:		DATE:		
	EDAC INC TORONTO, ONTARIO CANADA) QUALITY & SERVICE	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC.,AND SHALL NOT BE REPRODUCED,OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	SCALE: (IN C.A.D. 1:1)		SHEET 1 OF	2	
			DRAWING NUMBER: 629-3W3-250-3		250-3N4	ISSUE	
YOUR CONNECTION TO			PART NUMBER: 62	29-3W3-	250-3N4	1	

1000V AC rms



OPERATING TEMPERATURE:

.X ±0.25 .XX ±0.13 .XXX ±0.05

INSULATOR RESISTANCE: DIELECTRIC

WITHSTANDING VOLTAGE:

-55°C ~ 125°C



	-
COMPLIANT	:

THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.

