


SC-35-SD040J Aliases (UALSC35SD040J0)

KEMET, SC Three Phase, AC Line Filters, Common Mode, 0.04 mH



Click here for the 3D model.

Dimensions	
D	80mm MAX
Т	62mm MAX
Н	65mm MAX
LL	5mm +/-2mm
S	31mm NOM
S1	48mm NOM
Wire Size	2.0mm x 2P

Packaging Specifications

Packaging	Tray
Packaging Quantity	18
Component Weight	306.2 g

General Informatio	n
Series	SC Three Phase
Style	Through-Hole
Features	High Impedance
RoHS	Yes
Notes	Lead Spacing (S/S1) Are For Reference Only.
Miscellaneous	Temperature Rise Maximum: 55 K.
Core	Mn-Zn Ferrite

Specifications	
Voltage AC	250 VAC
Voltage DC	250 VDC
Inductance	0.04 mH (100 kHz)
Current	35 A
Temperature Range	-25/+120°C
DC Resistance	2 mOhms

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.