



VMDSC15-25-M4-40-Z/25PK

Ruland VMDSC15-25-M4-40-Z/25PK, Vibration Isolation Mount, 15mm OD, M4 Threaded Stud, 10mm Stud Lengths, 25mm Height, 40 Shore A Natural Rubber Jacket, Steel

25 pack



Description

Ruland VMDSC15-25-M4-40-Z/25PK is a 25 pack of vibration isolation mounts, each with two threaded studs. An individual isolation mount has a 15mm outside diameter, M4 threaded stud, 10mm stud lengths, and 25mm height. Vibration isolation mounts are used to dampen shock loads and reduce noise and wear on industrial equipment such as motors, conveyors, compressors, fans, or pumps which allows for a safer and more pleasant working environment. They are often referred to as a sandwich mount or rubber buffer because they function as a shock or vibration isolator sandwiched between two machine components or surfaces. A vibration isolation mount can be mounted to the system by passing it through an unthreaded hole and securing with a nut or threading it directly into tapped holes on the components it will be mounted to. The rubber jackets are made from natural rubber which has good elasticity and is well suited for most industrial equipment. Vibration isolation mounts in this pack have 40 Shore A hardness for high dampening and shock absorption. Bodies are made from zinc plated steel allowing for high strength suitability in most industrial applications. These vibration isolation mounts are manufactured by Otto Ganter, inventoried by Ruland, and RoHS3 compliant.

Product Specifications

Outer Diameter (OD)	0.59 in (15 mm)	Height (H1)	0.98 in (25 mm)
Thread (TH)	M4 x 0.7	Plate Thickness (PT)	0.06 in (1.4 mm)
Stud Length (LS)	0.39 in (10 mm)	Tapped Hole Depth (LT)	0.39 in (9.9 mm)
Spring Rate	114 lb/in (20 N/mm)	Shore Hardness	40A (+/- 5)
Max Deflection	0.25 in (6.4 mm)	Max Axial Load	28.1 lb (125 N)
Multipack Quantity	25	Geometry	Cylindrical
Rubber Material	Natural Rubber	Metal Material	Zinc Plated Steel
Metallic Body Finish	Zinc-Plated	Country of Origin	Hungary
Weight (lbs)	0.468500	UPC	634529360316
Tariff Code	4016.99.6000	UNSPC	31162804
Note 1	Performance ratings are for guidance only. The user must determine suitability for a particular application.		